







	<a href="#">POE SWITCH / EXTENDER PFT1310 3-PORT</a>	<a href="#">MOUNTING CLAWS LE-665099 LEGRAND</a>	<a href="#">SMART ROLLER GATE CONTROLLER ROLLERGATE/BLEBOX Wi-Fi, 230 V AC</a>	<a href="#">ELECTRICAL INSTALLATION BOX INTO THERMAL INSULATION KUZ-VOL-KB KOPOS</a>	<a href="#">SMART GARAGE DOOR CONTROLLER ATLO-GDC3: TUYA Wi-Fi, Tuya Smart</a>	<a href="#">EXTENDER HDMI+USB-EX-100</a>
						
	19.37 EUR 19.37 EUR	0.39 EUR 0.39 EUR	88.56 EUR 88.56 EUR	41.82 EUR 41.82 EUR	14.53 EUR 14.53 EUR	105.16 EUR 105.16 EUR
Application	...	Niloe, Valena Life product series	roller gates	...	garage doors	...
Rated voltage	...	...	230 V AC	...	...	...
Number of sections	...	...	...	1, 2	...	...
Maximal total load	...	...	2 x 1250 VA	...	...	...
Total maximal current	...	...	2 x 5 A	...	...	...
Voltage insulation	...	...	...	~ 400 V	...	...
Supported HDMI resolutions	...	...	...	...	...	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Maximal transmission range	...	...	...	...	...	100 m UTP cat. 5e, 6
LAN ports	• 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af)	...	...	...	...	...
Max. number of receivers working in the same time	...	...	...	...	...	253
Number of inputs	...	...	• 4 control, • 2 security	...	1 x Reed switch	...
Break distance	...	...	...	...	3 ... 15 mm	...
Protocols	...	...	...	...	...	HDBiT
Number of outputs	...	...	• 2 control, • 1 signaling	...	1 x Motor	...
Management	—	...	...	...	...	...
Main features	...	...	...	...	...	<ul style="list-style-type: none"> <li>• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse</li> <li>• The devices do not require direct connection, they also operate via the LAN network</li> <li>• Audio transmission via network</li> </ul>
Connector type	...	...	screw terminals	...	...	...
LED diodes	LAN, PoE	...	...	...	...	...
Transmission speed	10 / 100 Mbps	...	...	...	...	...
Wireless	...	...	Wi-Fi, 2.4 GHz - IEEE 802.11g	...	Wi-Fi, 2.4 GHz - IEEE 802.11b/g/n	...
Mobile phones support	...	...	<ul style="list-style-type: none"> <li>• The <a href="#">wBox</a> free application on Android</li> <li>• The <a href="#">wBox</a> free application on iOS</li> </ul>	...	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	...
Material	...	...	...	Non-halogen plastic	...	...
Maximal output power	• 15.4 W @ port PoE - First device • 3 W @ port PoE - Second device in cascade	...	...	...	...	...
Permissible relative humidity	...	...	...	...	...	0 % ... 90 % (non-condensing)
Power consumption	0.3 W	...	...	...	...	...
Thickness of the insulating layer	...	...	...	120 ... 330 mm	...	...
Mounting holes distance	...	...	...	60 mm, 71 mm	...	...
Range	100 m - Input 100 m - Output	...	...	...	...	...
Protections	Overvoltage	...	...	...	...	...
Power supply	PoE (802.3af/at)	...	...	...	100 ... 240 V AC, 50 / 60 Hz	2 x 5 V DC / 1 A (power adapter included)
Operation temp. / Relative humidity	-30 ... 65 °C / 10 ... 90 %	...	...	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> <li>• Possibility to connecting in cascade</li> <li>• The device can function as a LAN network and PoE power extender</li> </ul>	...	<ul style="list-style-type: none"> <li>• Roller gate control in cooperation with security modules (photozell, barrier, sensing edge),</li> <li>• Multiple users support from anywhere,</li> <li>• Control many objects from one app,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Keyboard built-in - 3 Touch control keys,</li> <li>• Backlit, touch control panel</li> <li>• Omnidirectional antenna Wi-Fi 5 dB,</li> <li>• SMA-RP socket</li> <li>• Range : 100 m (in open area), 40 m (internal)</li> <li>• µWiFi technology support</li> </ul>	<ul style="list-style-type: none"> <li>• for insulating systems</li> <li>• temperature range : -25 °C ... 60 °C</li> <li>• flammability index : 850 °C</li> <li>• adjustable depth of the box</li> <li>• Guides for attaching the TS35 rail</li> <li>• Expansion plugs, Mounting screws, opening lid, rubber gasket - included</li> </ul>	<ul style="list-style-type: none"> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Magnetic contact included</li> <li>• Garage door open alarm</li> <li>• Opening and closing history</li> <li>• STATUS indicator</li> <li>• ON/OFF button</li> <li>• For indoor use</li> </ul>	<ul style="list-style-type: none"> <li>• The need for a separate power supply for the transmitter and receiver</li> </ul>
Housing	Plastic, DIN, TS-35 rail mounting	...	Self-extinguishing , Surface-mounted (box)	...	...	...
"Index of Protection"	...	...	IP44	IP30 / IP44	...	...
Color	...	Black	Gray / Black	Light gray	...	...
Operation temp	...	...	-20 °C ... 50 °C	...	-10 °C ... 40 °C	-10 °C ... 60 °C
Weight	0.05 kg	0.001 kg	0.37 kg	0.735 kg	0.16 kg	0.168 kg
Dimensions	79 x 52 x 23 mm	33 x 19 x 7 mm	<ul style="list-style-type: none"> <li>• 129 x 96 x 57 mm - without antenna</li> <li>• 285 x 96 x 57 mm - with antenna, vertical</li> <li>• 197 mm - Antenna</li> </ul>	<ul style="list-style-type: none"> <li>196 x 156 x 86 ... 146 mm (box)</li> <li>210 x 170 x 12 mm (cover)</li> <li>120 x 120 x 200 mm (carrier)</li> </ul>	<ul style="list-style-type: none"> <li>• 44 x 39 x 23 mm</li> <li>• 5 m (cable length) - Reed switch</li> <li>• 0.45 m (cable length) - Power supply</li> </ul>	110 x 89 x 26 mm - Transmitter or receiver dimensions
Manufacturer / Brand	...	LEGRAND	BleBox	KOPOS	...	...
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years