

	IP CAMERA DS-2CD1043G2-LIU(2.8MM) Smart Hybrid Light - 3.7 Mpx Hikvision	POWER DISTRIBUTION UNIT PR-1.5M-4G/B (4 OUTLETS) 1.3 m
		
	166.15 EUR 166.15 EUR	3.71 EUR 3.71 EUR
Standard	TCP/IP	...
Sensor	1/3 " Progressive Scan CMOS	...
Rated voltage	...	220 ... 240 V AC / 50 Hz
Matrix size	4 Mpx	...
Total maximal current	...	10 A
Maximal total load	...	2500 W
Number of outlets	...	4 grounded outlets 10A/250V CEE 7/5
Fuse	...	—
Switch	...	—
Wire gauge	...	3 x 1.5 mm ²
Length of the cable	...	1.3 m
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	2.8 mm	...
View angle	• 98 ° (manufacturer data) • 93 ° (our tests result)	...
White light LED illuminator range	30 m	...
Range of IR illumination	30 m	...
Memory card slot	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	• Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Noise and echo reduction	...
Main stream frame rate	• 20 fps @ 3.7 Mpx • 25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...

Main features	<ul style="list-style-type: none"> • Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Auto White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Configurable Privacy Zones • Sharpness - sharper image outlines • Smart motion detection (with recognizing people and vehicles) 	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 6.5 W @ PoE • ≤ 5 W @ 12 V DC 	...
Housing	Compact - Metal + Plastic	Plastic
Color	White	Black
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.28 kg	0.26 kg
Dimensions	171 x 66 x 69 mm	196 x 54 x 39 mm
Supported languages	Polish, English, Croatian, Czech, Romanian, Serbian, Slovak, Slovenian, Turkish, Ukrainian, Vietnamese	...
Manufacturer / Brand	Hikvision	...

SAP Code	311322028	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00