





	EXTENDER ETHERNET+PoE ETH- ETH500-SET ATTE	NORMALLY OPEN RELAY MODULE PK4-12-ZD DELTA	MOUNTING PANEL A10- FRAME
			
	60.48 EUR 60.48 EUR	21.68 EUR 21.68 EUR	11.83 EUR 11.83 EUR
Housing type	1 U Rack 10"
Number of relay outputs	...	4	...
Material	Metal
Color	Black
LAN ports	2 x RJ45 10/100 Base-T + Passive PoE
Current consumption	...	35 mA per each relay at voltage 12 V DC	...
LED diodes	LAN, PoE, 10Mb
UTP transmission range	< 800 m (max)
Relay maximal load	...	10 A (max), 30 V DC / 50 V AC (max)	...
Transmission speed	10 / 100 Mbps : 2 LAN & PoE ports
Output	...	4 x NO/NC	...
Application	...	relay for electromagnetic lock/electric strike	...
Maximal output power	< 250 m - 100 Mbps - 50 W < 500 m - 100 Mbps - 25 W < 800 m - 10 Mbps - 15 W
Maximal total power	50 W
Operation temp	...	-10 °C ... 40 °C	...
Main features	<ul style="list-style-type: none"> • Can be powered from a switch (PoE 802.3at/af, Passive PoE) and via screw connectors • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender • The output PoE voltage is equal to the input voltage 	<ul style="list-style-type: none"> • DIN, TS-35 rail mounting, • LED indication, • Protections : Overvoltage, Reverse polarity connection 	...
Power supply	44 ... 58 V DC - Passive PoE 12 ... 58 V DC - screw connectors	10 ... 16 V DC	...
Power consumption	1.35 W
Weight	0.05 kg	0.08 kg	0.19 kg
Dimensions	73 x 52 x 20 mm (single element)	73 x 44 x 40 mm	256 x 44 x 21 mm

Manufacturer / Brand	ATTE	DELTA	DELTA
Guarantee	3 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00