



	TIME & ATTENDANCE RECORDER ASA3213G-MW DAHUA	EXTENDER ETHERNET+PoE EXT-POE3 PULSAR
		
	406.98 GBP 406.98 GBP	25.23 GBP 25.23 GBP
Sensor	CMOS	...
Number of inputs	...	1 pcs - RJ-45 socket
Matrix size	2 Mpx	...
Number of outputs	...	3 pcs - RJ-45 socket
Resolution	1920 x 1080 - 1080p	...
Output voltage	...	Compatible with the power supply voltage
Standard	TCP/IP	...
Output current	...	<ul style="list-style-type: none"> • 0.6 A - PoE OUT 1/2 ports - Compliance with PoE (802.3af/at) • 0.3 A - Port PoE OUT 3 - Passive PoE Total max. 0.6 A
IR illuminator	✓	...
LED illuminator	✓	...
Input power pairs PoE IN	...	1/2 (+) 3/6(-) 4/5 (+) 7/8 (-)
Temperature measurement	—	...
Temperature measurement range	—	...
Output power pairs PoE OUT1/2	...	4/5 (+) 7/8 (-) - Passive PoE
Accuracy of temperature measurement	—	...
Ethernet interface	...	10/100 Mb/s
Protections	...	<ul style="list-style-type: none"> • Short-circuit • Overload
Face recognition distance	0.3 m ... 1.5 m (max 500 faces in the database)	...
Operation state indication	...	LED diodes
RFID proximity reader built-in	<ul style="list-style-type: none"> • 13.56 MHz S50 • Memory of 500 RFID cards 	...
Operation temp	...	-10 °C ... 40 °C
Internal memory	Support storage of 150 000 records	...

Video output	—	...
RS-485 interface	✓	...
RS-232 interface	—	...
Wiegand interface	—	...
USB	1 x USB 2.0	...
Memory card slot	—	...
Alarm inputs / outputs	1 / 1 - Relay outputs	...
Audio	Voice message	...
Network interface	1 x 10/100 Base-T (RJ-45)	...
Network protocols	IPv4, RTSP, RTP, TCP, UDP, P2P	...
WEB Server	Built-in	...
ONVIF	—	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • 500 users • Software update via network • Real-time Surveillance • Multiple Authentication • Take face image after swiping card • Auto-Registration • Recording of information about Time&Attendance • Statistical Reporting • Backup to USB drive (pendrive, external drive) • Output button support • Door status detection • Lock control • Tamper protections 	...

Power supply	12 V DC / 1.5 A (power adapter included)	Compliance with PoE (802.3af/at) : 44 V ... 57 V DC
Power consumption	≤ 18 W	...
Housing	Plastic (ABS)	...
Color	Black + Silver	...
"Index of Protection"	—	...
Operation temp	-10 °C ... 55 °C	...
Weight	<ul style="list-style-type: none"> • 0.22 kg (without stand) • 0.24 kg (with stand) 	0.11 kg
Dimensions	<ul style="list-style-type: none"> • 116 x 107 x 22 mm (without stand) • 116 x 107 x 78 mm (with stand) 	87 x 77 x 25 mm
Supported languages	English	...
Manufacturer / Brand	DAHUA	PULSAR
Guarantee	3 years	2 years