





|                           | <a href="#">TRIPLE SMART LED LIGHTING CONTROLLER ATLO-SW3-TUYA Wi-Fi, Tuya Smart</a>   | <a href="#">QUAD SMART LED LIGHTING CONTROLLER ATLO-SW4-TUYA Wi-Fi, Tuya Smart</a>   | <a href="#">CABLE OUTLET DPK1.01/11-SIMON54</a>                                    | <a href="#">EXTENDER ETHERNET+PoE LR1002-1EC-V3 RECEIVER DAHUA</a>  |
|---------------------------|--|--|--|---|
|                           |   |   |  |    |
|                           | 13.19 GBP<br>13.19 GBP   | 16.73 GBP<br>16.73 GBP   | 4.47 GBP<br>4.47 GBP   | 22.48 GBP<br>22.48 GBP  |
| LAN ports                 | ...  | ...  | ...  | 1 pcs RJ45  |
| Application               | switching devices on/off   | switching devices on/off   | ...  | ...   |
| Transmission ports        | ...  | ...  | ...  | 1 pcs BNC   |
| Number of channels        | 3  | 4  | ...  | ...   |
| Support                   | ...  | ...  | Simon 54 product series, for Nature, Premium frames                                | ...   |
| Number of modules         | ...  | ...  | 1  | ...   |
| Transmission speed        | ...  | ...  | ...  | 10 / 100 Mbps   |
| Maximal total load        | 3 x 150 W  | 4 x 150W W   | ...  | ...   |
| Total maximal current     | 3 x 3.3 A  | 4 x 2.5 A  | ...  | ...   |
| Number of inputs          | 3  | 4  | ...  | ...   |
| Transmission range        | ...  | ...  | ...  | max. 1000 m @ 10 Mbps ,<br>max. 400 m @ 100 Mbps<br>The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver |
| Number of outputs         | 3  | 4  | ...  | ...   |
| Protections               | ...  | ...  | ...  | Overvoltage   |
| Connector type            | screw terminals  | screw terminals  | ...  | ...   |
| Wireless                  | <ul style="list-style-type: none"> <li>• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n</li> <li>• Bluetooth</li> </ul>  | <ul style="list-style-type: none"> <li>• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n</li> <li>• Bluetooth</li> </ul>  | ...  | ...   |
| Radio communication range | < 100 m (open area)  | < 100 m (open area)  | ...  | ...   |
| Mobile phones support     | <ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul> | <ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul> | ...  | ...   |
| Power supply              | 100 ... 240 V AC, 50 / 60 Hz   | 100 ... 240 V AC, 50 / 60 Hz   | ...  | 48 V ... 57 V DC  |
| Manufacturer / Brand      | ...  | ...  | KONTAKT Simon  | DAHUA   |

|                       |  |  |  |  |
|-----------------------|--|--|--|--|
| Main features         | <ul style="list-style-type: none"> <li>• Local control by physical button ,</li> <li>Tuya Smart :</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• The ability to set the default status of the device after a power failure</li> </ul> | <ul style="list-style-type: none"> <li>• Local control by physical button ,</li> <li>Tuya Smart :</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• The ability to set the default status of the device after a power failure</li> </ul> | <ul style="list-style-type: none"> <li>• Cable diameter : 6.2 ... 14.5 mm</li> <li>• Claw or screw mounting</li> <li>• Installation in flush-mounted enclosures</li> <li>• Aesthetic and solid construction</li> </ul> | <ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Easy installation - doesn't require any configuration of IP nor MAC address</li> <li>• Power supply PoE - pins 1, 2 and 3, 6</li> <li>• Supports long range power supply transmission via coaxial cable</li> <li>• The device operates from the PoE switch side</li> <li>• Possibility to mount on a wall, or on the DIN TS-35 rail</li> </ul> |
| Housing               | Plastic  | Plastic  | Non-halogen plastic, PC  | ...  |
| "Index of Protection" | IP20   | IP20   | IP20   | ...  |
| Color                 | White  | White  | White (RAL 9003)   | ...  |
| Operation temp        | -10 °C ... 40 °C   | -10 °C ... 40 °C   | ...  | ...  |
| Weight                | 0.03 kg  | 0.03 kg  | 0.048 kg   | 0.07 kg  |
| Dimensions            | 43 x 39 x 22 mm  | 43 x 39 x 22 mm  | <ul style="list-style-type: none"> <li>• 75 x 75 x 55 mm</li> <li>• 22 mm - mounting depth</li> </ul>  | 79 x 64 x 23 mm  |
| Guarantee             | 2 years  | 2 years  | 6 years  | 3 years  |