



	STRAIGHT CABLE DUCTING LS-20X18/B STASINSKI	COAXIAL CABLE TRI-LAN-400 50 Ω
		
	2.96 EUR 2.96 EUR	2.79 EUR 2.79 EUR
Width	20 mm	...
Height	18 mm	...
Length	2000 mm	...
In section	...	100 m . Price for 1m when buying a whole roll
Material	PVC	...
Color	Black	...
Inner conductor	...	Ø 2.7 mm Cu ± 0.02 mm Wire
Operation temp	-5 °C ... 60 °C	...
Dielectric	...	Ø 7.2 mm Physical foam
"Index of Protection"	IP30	...
Shield	...	Foil - Al/PET
Weight	0.286 kg	...
Manufacturer / Brand	STASINSKI	...
Braid	...	168 x Ø 0.15 mm Stranded wire CuSn
Impedance	...	50 Ω
Outer coating	...	Ø 10.3 mm ± 0.20 mm PE
Main features	Compliance with PN-EN 50085-2-1:2008+A1:2011, PN-EN 50085-1:2010+A1:2013-10 standards	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -40 °C ... 70 °C

Cable attenuation at 100m section	...	Temperature : 20 °C 2.3 dB @ 30 MHz 3.0 dB @ 50 MHz 4.9 dB @ 150 MHz 6.0 dB @ 220 MHz 8.7 dB @ 450 MHz 12.8 dB @ 900 MHz 17.0 dB @ 1500 MHz 18.8 dB @ 1800 MHz 20.0 dB @ 2000 MHz 22.7 dB @ 2500 MHz 37.6 dB @ 5800 MHz
Maximum transmitted power	...	3.36 kW @ 30 MHz 2.59 kW @ 50 MHz 1.47 kW @ 150 MHz 1.20 kW @ 220 MHz 0.82 kW @ 450 MHz 0.57 kW @ 900 MHz 0.43 kW @ 1500 MHz 0.39 kW @ 1800 MHz 0.36 kW @ 2000 MHz 0.32 kW @ 2500 MHz 0.20 kW @ 5800 MHz
Guarantee	2 years	2 years

