




	VIDEO SEPARATOR D-SEP/HD-4	CONNECTION BOX PHW-75X75/EPN IP67 Elektro-Plast
		
	85.00 PLN 85.00 PLN	17.94 PLN 17.94 PLN
Number of intakes	...	4 - Cable glands PG-16
"Index of Protection"	...	IP67
Cable diameter	...	10 ... 14 mm
Main features	...	<ul style="list-style-type: none"> • Surface mount • Cover mounting with screws • The set includes a 5 x 4 mm² insert • Compliance with PN-EN 60670-1 standards
Material	...	Non-halogen plastic
Standard	<ul style="list-style-type: none"> • AHD - 8 Mpx, 4K UHD • HD-CVI - 8 Mpx, 4K UHD • HD-TVI - 8 Mpx 4K UHD • CVBS - PAL / NTSC 	...
Color	...	Gray
Device type	Passive	...
Number of inputs	4 pcs BNC socket	...
Number of outputs	4 pcs BNC socket	...
Input impedance	75 Ω	...
Output impedance	75 Ω	...
Opto-isolation between inputs and outputs	50 V DC	...
Galvanic separation between individual channels	> 2000 V	...
Attenuation	<ul style="list-style-type: none"> • 4.43 MHz @ 0.37 dB • 11 MHz @ 0.47 dB • 21 MHz @ 0.62 dB • 38 MHz @ 0.93 dB • 42 MHz @ 0.93 dB • 67.5 MHz @ 1.16 dB 	...
Bandwidth	200 MHz	...
Inputs protection	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air EFT, IEC 61000-4-4, 40A (5/50ns) Lightning, IEC 61000-4-5, 30A (t _p =8/20μs)	...
Power supply	—	...

Operation temp	-20 °C ... 55 °C	...
Weight	0.12 kg	...
Dimensions	103 x 78 x 30 mm	85 x 85 x 41 mm - External dimensions , 75 x 75 x 33 mm - Internal dimensions
Manufacturer / Brand	DELTA	Elektro-Plast
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00