





	IP CAMERA IPC-HDW2241T-ZS-27135 WizSense - 1080p 2.7 ... 13.5 mm - MOTOZOOM DAHUA	CYLINDRICAL MAGNETIC CONTACT B-2FLF SATEL	POWER DISTRIBUTION UNIT L19/6VP	ALKALINE BATTERY BAA-MAXPLUS*P4 1.5 V LR6 (AA) ENERGIZER	CEILING BRACKET FOR DOME CAMERAS BD-CV94B
					
	346.21 EUR 346.21 EUR	3.37 EUR 3.37 EUR	19.65 EUR 19.65 EUR	3.04 EUR 3.04 EUR	0.39 EUR 0.39 EUR
Neck diameter	...	...	...	...	Ø 94 mm
Detection	...	Opening the door or window	...	...	...
Standard	TCP/IP	...	...	...	...
Maximum reed switched voltage	...	100 V	...	...	...
Total maximal current	...	...	16 A	...	...
Suitable for cameras	...	...	...	...	APTI-24V2-36B, DP-954HHD/IRD
Maximal switched current	...	500 mA	...	...	...
Sensor	1/2.8 " Progressive Scan CMOS	...	...	...	...
Maximal total load	...	...	3500 W	...	...
Material	...	...	...	...	Metal
In package	...	...	...	4 pcs The price for package	...
Make distance	...	15 mm	...	...	...
Matrix size	2.1 Mpx	...	...	...	...
Rated voltage	...	...	230 V AC / 50 Hz	1.5 V	...
Break distance	...	20 mm	...	...	...
Number of outlets	...	...	6 for universal plug 230 V (Schuko)	...	...
Distance from mounting surface	...	...	...	...	58 mm
Type (size)	...	...	...	LR6 (AA)	...
Assembly	...	...	In RACK 19" cabinets	...	...
Length of the power cable	...	...	1.8 m	...	...
Housing type	...	...	1 U RACK 19"	...	...
Switch	...	...	Yes (with built-in LED indicator)	...	...
Resolution	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...	...	...	...
Main features	...	<ul style="list-style-type: none"> <li>Length of the cable : 45 cm</li> <li>Mounting hole diameter for the sensor : 15 mm</li> <li>Medium-sized body with a round flange</li> </ul>	<ul style="list-style-type: none"> <li>Overvoltage protection</li> <li>LED indicators displaying the device's operating status</li> </ul>	<ul style="list-style-type: none"> <li>Longest Lasting Alkaline Batteries,</li> <li>Powerful and high performance,</li> <li>Holds power for up to 12 years of shelf life,</li> <li>Leak-proof construction</li> </ul>	...
Lens	2.7 ... 13.5 mm - Motozoom	...	...	...	...
View angle	<ul style="list-style-type: none"> <li>108 ° ... 30 ° (manufacturer data)</li> <li>103 ° ... 31 ° (our tests result)</li> </ul>	...	...	...	...
Range of IR illumination	40 m	...	...	...	...
RS-485 interface	—	...	...	...	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...	...	...	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...	...	...
Alarm inputs / outputs	—	...	...	...	...
Audio	<ul style="list-style-type: none"> <li>Microphone built-in</li> <li>Audio detection</li> <li>Audio transmission via network</li> </ul>	...	...	...	...
Network interface	10/100 Base-T (RJ-45)	...	...	...	...
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, Multicast, ICMP, IGMP	...	...	...	...
WEB Server	Built-in, Web Viewer	...	...	...	...
Max. number of on-line users	6	...	...	...	...
ONVIF	21.06	...	...	...	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>Android: Free application <a href="#">DMSS</a></li> <li>iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>	...	...	...	...
Default IP address	192.168.1.108	...	...	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...	...	...
Web browser access ports	80, 37777	...	...	...	...
PC client access ports	37777	...	...	...	...
Mobile client access ports	37777	...	...	...	...
Port ONVIF	80	...	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...	...	...	...
Main stream frame rate	25 fps @ 1080p	...	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Motozooom lens - Controlling from browser, NVR or software</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC - configurable Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Day/night mode</li> <li>• Configurable Privacy Zones</li> <li>• IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles</li> </ul>	...	...	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 530 mA</li> </ul>	...	...	...	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 5.7 W @ 12 V DC</li> <li>• ≤ 6 W @ PoE</li> </ul>	...	...	...	...
Housing	Dome - Metal	...	...	...	...
Color	White	White	...	...	Black
Vandal-proof	—	...	...	...	...
"Index of Protection"	IP67	...	...	...	...
Operation temp	-30 °C ... 60 °C	...	...	...	...
Weight	0.69 kg	0.006 kg	0.75 kg	0.024 kg	0.18 kg
Dimensions	Ø 122 x 108 mm	Ø 18 x 6.3 mm (with flange)	482 x 45 x 54 mm	...	Ø 94 x 58 mm
Supported languages	Polish, English	...	...	...	...
Manufacturer / Brand	DAHUA	SATEL	...	ENERGIZER	...
Guarantee	3 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00