



	<a href="#">REMOTE CONTROL SREMOTE/BLEBOX Wi-Fi</a>	<a href="#">SMART SWITCH SWITCHBOX-V3/BLEBOX Wi-Fi 230 V AC</a>	<a href="#">NVR DS-7732NXI-I4/S(E) 32 CHANNELS ACUSENSE Hikvision</a>
			
	701.54 CZK 701.54 CZK	947.35 CZK 947.35 CZK	32669.54 CZK 32669.54 CZK
Standard	...	...	TCP/IP
Application	...	switching devices on/off	...
Supported resolutions	...	...	max. 32 Mpx
Rated voltage	...	230 V AC	...
Maximal total load	...	3500 W / 3680 VA	...
Total maximal current	...	16 A	...
Number of inputs	...	1	...
Video outputs	...	...	2 pcs HDMI 4K 1 pcs VGA 1 pcs CVBS There is a possibility to configure a SPOT function on one of the output
Number of outputs	...	1	...
Connector type	...	screw terminals	...
Operation range	≤ 100 m (in open area) ≤ 40 m (internal)	...	...
Audio support	...	...	<ul style="list-style-type: none"> <li>• 32 Channels - Audio from cameras</li> <li>• Bi-directional audio streaming support</li> </ul>
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
Audio inputs	...	...	1 pcs CINCH
Audio outputs	...	...	1 pcs CINCH
Image compression method	...	...	H.265+ / H.265 / H.264+ / H.264
Bitrate	...	...	max. 256 Mbps
Supported hard drives	...	...	4 x 10 TB SATA + 1 x eSATA
Recording modes	...	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	...	Backup to USB drive (pendrive, external drive)
Main features	<ul style="list-style-type: none"> <li>• Number of buttons : 4,</li> <li>• Number of supported devices : max. 7,</li> <li>• Configurable Buttons</li> <li>• Ability to assign a device to a button</li> <li>• Controlling BleBox devices</li> <li>• LED indication</li> <li>• Order confirmation</li> <li>• Bidirectional communication</li> <li>• Transmission encryption</li> <li>• µWiFi technology support</li> <li>• Control possible without Wi-Fi network available</li> <li>• Integrated magnets to attach to metal surfaces</li> </ul>	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• The ability to set the default status of the device after a power failure,</li> <li>• Energy consumption metering,</li> <li>• µWiFi technology support</li> </ul>	...

Searching and playback the records	...	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function Records playback from max. 16 channels in the same time @ 1080p
Housing	Plastic (ABS)	Plastic	...
"Index of Protection"	...	IP20	...
Color	White	Black	...
Network interface	...	...	2 x RJ-45 10/100/1000 Base-TX
Network functions	...	...	<ul style="list-style-type: none"> <li>Live image view, Playback the records, Backup the records</li> <li>max. 128 on-line users - iVMS-4200 application</li> </ul>
Network protocols	...	...	TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS
ONVIF	...	...	✓
Default IP address	...	...	192.168.1.64
Default admin user / password	...	...	admin / - The administrator password should be set at the first start
Mobile phones support	<ul style="list-style-type: none"> <li>The <a href="#">wBox</a> free application on Android</li> <li>The <a href="#">wBox</a> free application on iOS</li> </ul>	<ul style="list-style-type: none"> <li>The <a href="#">wBox</a> free application on Android</li> <li>The <a href="#">wBox</a> free application on iOS</li> </ul>	Port no.: 8000 or access by a cloud (P2P) Android: Free application <a href="#">Hik-Connect</a> iOS: Free application <a href="#">Hik-Connect</a>
Web browser access ports	...	...	80, 8000
PC client access ports	...	...	8000
Mobile client access ports	...	...	8000
RTSP URL	...	...	<ul style="list-style-type: none"> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li> </ul>
USB	...	...	2 pcs USB 2.0 1 pcs USB 3.0
Serial ports	...	...	2 pcs RS-485 1 pcs RS-232
Alarm inputs / outputs	...	...	16 / 9
PTZ control	...	...	<ul style="list-style-type: none"> <li>IP Speed Dome Cameras</li> <li>RS-485 - PELCO-D/P and others</li> </ul>
Motion Detection	...	...	2.0
Intelligent image analysis	...	...	✓

Main features	...	...	<ul style="list-style-type: none"> <li>• NVR from the AcuSense series</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, Face recognition, Motion detection with human/vehicle silhouette recognition</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Comparison of faces with images from the database</li> <li>• supports 4 types of facial attributes extraction</li> <li>• Support for up to 16 face databases, including 50 000 face images</li> <li>• Smart search for a person based on a face photo</li> <li>• Cooperation with POS (Point of Sale) terminals</li> <li>• Power outputs : 12 V DC / 1 A, 12 V DC / 0.5 A (controlling)</li> </ul> <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> <li>• ANPR</li> <li>• people counting</li> </ul>
Mouse support	...	...	✓
IR remote controller in the set	...	...	—
Power supply	<ul style="list-style-type: none"> <li>• 2 x alkaline battery 1.5 V LR3 (AAA) (included)</li> <li>• Backup time ≤ 15 months</li> </ul>	...	100 ... 240 V AC / 50 ... 60 Hz
Power consumption	...	...	max. 30 W (without HDD)
Operation temp	-20 ... 50 °C	-20 °C ... 50 °C	-10 °C ... 55 °C
Weight	0.074 kg	0.04 kg	4.1 kg
Dimensions	148 x 46 x 16 mm	38 x 35 x 23 mm	445 x 402 x 75 mm, RACK 19", 1.5U
Supported languages	...	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	BleBox	BleBox	Hikvision
SAP Code	...	...	303618605
Guarantee	2 years	2 years	3 years

