




	<a href="#">POWER DISTRIBUTION UNIT PR-1.5M-3G-SW/B (3 OUTLETS) 1.3 m</a>	<a href="#">ACCESS CONTROLLER MODULE MC16-PAC-EX-2 ROGER</a>	<a href="#">HOUSING A19-TS-35/OB-4U</a>
			
	19.49 PLN 19.49 PLN	2130.00 PLN 2130.00 PLN	344.00 PLN 344.00 PLN
Width	...	...	19 "
Number of served transitions	...	2	...
Height	...	...	4 U
Inputs	...	12	...
Rated voltage	220 ... 240 V AC / 50 Hz	...	...
Material	...	...	Steel - powder painted
Outputs	...	8	...
Total maximal current	10 A	...	...
Maximal total load	2500 W	...	...
Number of users	...	max. 12000 - Number of identifiers	...
"Index of Protection"	...	...	IP20
Number of outlets	3 grounded outlets 10A/250V CEE 7/5	...	...
Application	...	...	RACK 19"
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.	...
Number of permissions per ID	...	100	...
Fuse	—	...	...
Buffer memory	...	8 000 000 events buffer	...
Switch	✓	...	...
MCT readers support	...	16 pcs	...
Wire gauge	3 x 1.5 mm <sup>2</sup>	...	...
Length of the cable	1.3 m	...	...
Housing	Plastic	...	...
Readers connections	...	4 pcs - Wiegand / PRT	...
Color	Black	...	Black (RAL 9005)
Number of login points	...	4	...
Number of access terminals	...	8	...
Number of access zones	...	4	...
Number of alarm zones	...	4	...
Number of automation nodes	...	4	...
Battery backup support	...	12 V / 7 Ah	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Communication	...	<ul style="list-style-type: none"> <li>• Ethernet - RJ-45 socket</li> <li>• RS-485 interface</li> <li>• RACS 5 v2 (Roger)</li> </ul>	...
Main features	...	<ul style="list-style-type: none"> <li>• Integrated support in VISO EX software</li> <li>• Functions in the VISO EX system: - MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system - unlimited</li> <li>- division of the system into partitions operated by independent operators</li> <li>- tool for integration with RACS5 (API) systems</li> <li>- integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)</li> </ul>	<ul style="list-style-type: none"> <li>• TH-35 rail</li> <li>• Corrosion resistance</li> <li>• Possibility to mount of 24 fuses, 1 S wide</li> <li>• 6-point fixing to the front RACK rails</li> <li>• 6 pcs. of M6 screws with cage nuts included</li> <li>• The enclosure features labeling field 420x20 mm</li> <li>• 10 rubber bushings in the top and bottom part of the enclosure</li> <li>• Mounting plate for a 17Ah/12V battery included</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• 17 ... 22 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>	...
Operation temp	...	5 °C ... 40 °C	-10 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)	...
Weight	0.27 kg	0.14 kg	3.73 kg
Dimensions	184 x 54 x 46 mm	175 x 72 x 30 mm	<ul style="list-style-type: none"> <li>• 445 x 170 x 155 mm Internal dimensions</li> <li>• 481.5 x 175 x 234 mm External dimensions</li> </ul>
Manufacturer / Brand	...	ROGER	PULSAR
Guarantee	2 years	3 years	2 years