





	<a href="#">SMART GARAGE DOOR CONTROLLER ATLO-GDC2-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">SMART DUAL VALVE FOR THE IRRIGATION SYSTEM ATLO-VR2G-BLE-TUYA Bluetooth BLE, Tuya Smart</a>	<a href="#">AHD, HD-CVI, HD-TVI CAMERA APTI-H53V21-36W - 8.3 Mpx 4K UHD 3.6 mm</a>	<a href="#">POWER DISTRIBUTION UNIT MCE-10 (10 OUTLETS) 1.5 m MACLEAN</a>
				
	15.92 USD 15.92 USD	55.85 USD 55.85 USD	37.03 USD 37.03 USD	14.72 USD 14.72 USD
Rated voltage	...	...	...	230 V AC / 50 Hz
Application	garage doors	irrigation control - 2 Zones	...	...
Total maximal current	...	...	...	16 A
Type (size)	...	3/4 "	...	...
Standard	...	...	AHD, HD-CVI, HD-TVI	...
Maximal total load	...	...	...	3680 W
Sensor	...	...	1/2.5 " Progressive Scan CMOS	...
Matrix size	...	...	8.3 Mpx	...
Number of inputs	1 x Reed switch	...	...	...
Working pressure	...	0.05 ... 0.8 MPa / 7.25 ... 116 psi	...	...
Number of outputs	1 x NO	...	...	...
Number of outlets	...	...	...	2 x 5 grounded outlets 16A/250V, E type ( CEE 7/5 )
Break distance	3 ... 15 mm	...	...	...
Fuse	...	...	...	16 A / 250 V
Opening/closing time	...	5 ... 10 s	...	...
Switch	...	...	...	2 pcs - illuminated, each for a section of 5 outlets
Wire gauge	...	...	...	3 x 1.5 mm <sup>2</sup>
Length of the cable	...	...	...	1.5 m
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	• Bluetooth, • 2.4 GHz Wi-Fi IEEE 802.11 b/g/n - Bluetooth/Wi-Fi gateway	...	...
Radio communication range (at open area)	...	• 15 m - Bluetooth • The range limited only by the availability of the Wi-Fi network - Bluetooth/Wi-Fi gateway	...	...
Mobile phones support	• The <a href="#">Tuya Smart</a> free application on Android • The <a href="#">Tuya Smart</a> free application on iOS	• The <a href="#">Tuya Smart</a> free application on Android • The <a href="#">Tuya Smart</a> free application on iOS	...	...

Resolution	...	...	<ul style="list-style-type: none"> <li>• 3840 x 2160 - 8.3 Mpx 4K UHD @ AHD / HD-CVI / HD-TVI @ 12.5 fps, 15 fps</li> <li>• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI / HD-CVI @ 12.5 fps, 20 fps,</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 15 fps, 25 fps, 30 fps,</li> <li>• 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps</li> </ul>	...
Range of IR illumination	...	...	25 m	...
IR illuminator power adjustment	...	...	Automatic	...
Lens	...	...	3.6 mm	...
Main features	<ul style="list-style-type: none"> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Magnetic contact included</li> <li>• Garage door open alarm</li> <li>• Opening and closing history</li> <li>• STATUS indicator</li> <li>• ON/OFF button</li> <li>• For indoor use</li> </ul>	<ul style="list-style-type: none"> <li>• schedule,</li> <li>• timer,</li> <li>• manual watering (app or button),</li> <li>• delay after rain : 1 ... 7 days - the device will not turn on the sprinklers if it is raining,</li> <li>• remote access - Bluetooth/Wi-Fi gateway (included),</li> <li>• voice control</li> <li>• 2 x STATUS indicator</li> <li>• Low current consumption</li> <li>• Easy installation - the valve is mounted directly on the tap</li> <li>• 2 x 3/4" / 1/2" Adapter (included)</li> </ul>	...	...
View angle	...	...	<ul style="list-style-type: none"> <li>• 77 ° (manufacturer data)</li> <li>• 83 ° (our tests result)</li> </ul>	...
S/N ratio	...	...	> 50 dB	...
Video output	...	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	...
Operation temp	0 °C ... 40 °C	4.5 °C ... 45 °C	...	...
Main features	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• ICR - Movable InfraRed filter</li> <li>• DNR - Digital Noise Reduction</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
OSD menu	...	...	✓	...

Power supply	100 ... 240 V AC, 50 / 60 Hz	4 x 1.5V, type AA/LR6/FR6 battery (not included)	12 V DC / 260 mA	...
Power consumption	...	...	≤ 3.1 W	...
Housing	...	Plastic (ABS) + Nylon, UV-resistant, Waterproof	Dome - Metal	Plastic
Color	...	Gray + Black	White	Black
"Index of Protection"	...	IP55	IP67	...
Vandal-proof	...	...	—	...
Operation temp	...	...	-20 °C ... 60 °C	...
Weight	0.16 kg	0.4 kg	0.43 kg	0.968 kg
Dimensions	<ul style="list-style-type: none"> <li>• 90 x 39 x 25 mm</li> <li>• 5 m (cable length) - Reed switch</li> <li>• 1 m (cable length) - Power supply</li> </ul>	141 x 122 x 58 mm	Ø 97 x 91 mm	738 x 70 x 45 mm
Manufacturer / Brand	...	...	APTI	MACLEAN
Guarantee	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00