




	CONNECTION BOX PU-2D	CONNECTION BOX PU-4D	MICROWAVE RADAR DS-PR1-60 Hikvision
			
		65.62 SEK 65.62 SEK	27829.35 SEK 27829.35 SEK
Application	Outdoor
Sensor type	Microwave (MW)
Number of intakes	2 - Cable glands PG-9	4 - Cable glands PG-9	...
Recommended installation height	1.2 m ... 4 m
Range	60 m
Cable diameter	4 ... 8 mm	4 ... 8 mm	...
Detection angle	100 °
Sensitivity adjustment	Automatic
Network interface	10/100 Base-T (RJ-45)
Network protocols	HTTP, DNS, NTP, TCP, UDP, DHCP, ARP, SSH
Alarm outputs	3 pcs : 0.5 A / 125 V AC 1 pcs : 10 A / 240 V AC
LED indication	✓
Microwave frequency band	24 GHz
Pet immunity	max. 20 kg
Antimask feature	✓
Target speed range	-8.7 ... +8.7 m/s
Main features	<ul style="list-style-type: none"> • Maximum number of objects to be observed : 32 • Immunity to environmental changes • Creep zone control • Display the position and direction of an object and the path it has traveled through it • Detection of non-standard moving objects (crawling, squatting or kneeling) • Ability to work with up to 4 Speed Dome cameras for automatic tracking of objects detected by the radar • Tamper detection - opening the enclosure, removing from mounting surface • RESET button

Power supply	• 12 V DC / 500 mA • PoE (802.3at)
Power consumption	max. 10 W
Operation temp	-40 °C ... 65 °C
Color	White
"Index of Protection"	IP67	IP67	IP67
IK rating	IK09
Weight	1.84 kg
Dimensions	110 x 55 x 25 mm	100 x 100 x 37 mm	228 x 206 x 61 mm
Manufacturer / Brand	Hikvision
SAP Code	302401144
Guarantee	2 years	2 years	3 years

