



	IP SPEED DOME CAMERA OUTDOOR IPC94144SR-X25-F40C LightHunter - 4 Mpx 4.8 ... 120 mm UNIVIEW	SWITCHING ADAPTER EDR-150-24 MEAN WELL
		
	1258.03 USD 1258.03 USD	34.99 USD 34.99 USD
Adapter type	...	Switching
Standard	TCP/IP	...
Power voltage	...	<ul style="list-style-type: none"> • 90 ... 264 V AC • 127 ... 370 V DC
Output voltage	...	24 V DC
Sensor	<ul style="list-style-type: none"> • Camera PTZ : 1/2.7 " Progressive Scan CMOS • Camera 2 : 1/2.7 Progressive Scan CMOS 	...
Output voltage adjustment	...	24 ... 28 V DC
Maximal load	...	6.5 A
Output power	...	156 W
Number of outputs	...	1 pcs
Matrix size	<ul style="list-style-type: none"> • Camera PTZ : 4 Mpx • Camera 2 : 4 Mpx 	...
Efficiency	...	87 %
Housing type	...	DIN
Protections	...	<ul style="list-style-type: none"> • Short-circuit • Overload • Overvoltage • Overheat
Resolution	<ul style="list-style-type: none"> • 2688 x 1520 - 4 Mpx, • 1920 x 1080 - 1080p - Camera 2, • 1280 x 720 - 720p - Camera PTZ 	...
Operation temp. / Relative humidity	...	-20 °C ... 60 °C / 20 ... 95 %
Lens	<ul style="list-style-type: none"> • Camera PTZ : 4.8 ... 120 mm F1.5 • Camera 2 : 4 mm F1.6 	...
View angle	<ul style="list-style-type: none"> • Camera PTZ : 55 ° ... 3.1 ° • Camera 2 : 91 ° 	...
Optical zoom	x 25	...
Digital zoom	—	...
Range of IR illumination	<ul style="list-style-type: none"> • 100 m @ Camera PTZ • 30 m @ Camera 2 	...
Preset rotation speed	<ul style="list-style-type: none"> • 80 °/s (horizontal) • 80 °/s (vertical) 	...
Rotation speed (manual control)	<ul style="list-style-type: none"> • 0.1 °/s ... 80 °/s (horizontal) • 0.1 °/s ... 80 °/s (vertical) 	...
Horizontal rotation range	360 ° - continuous	...

Vertical rotation range	-15 ° ... 90 °	...
RS-485 interface	✓	...
Number of presets	1024	...
Horizontal scan	✓	...
Route settings	16	...
Image compression method	Ultra H.265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	2 / 1	...
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Audio detection • Speaker built-in - Alarm siren • Bi-directional audio streaming support • Digital Noise Reduction 	...
Main stream frame rate	<ul style="list-style-type: none"> • Camera PTZ : 25 fps @ 4 Mpx • Camera 2 : 25 fps @ 4 Mpx 	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	✓	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Mobile phones support	Port 37777 <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...

Main features	<ul style="list-style-type: none"> • Intelligent Object Tracking • Active deterrence function - Light and sound alarm • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Auto White Balance • Sharpness - sharper image outlines • Configurable: brightness, contrast, saturation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Configurable Privacy Zones • Motion Detection • Overvoltage protection : 6 kV • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, crowd gathering estimation, people counting, face detection 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 3 A (power adapter included) 	...
Power consumption	≤ 24 W	...
Housing	Speed Dome, Plastic	...
Color	White + Black	...
Operation temp	-40 °C ... 65 °C	...
"Index of Protection"	IP66	...
Weight	2.52 kg	0.51 kg
Dimensions	Ø 163 x 304 mm (without bracket)	127 x 126 x 41 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	MEAN WELL
Guarantee	3 years	2 years