



	AHD, HD-CVI, CVBS, TCP/IP DVR BCS-CVR0401-IV 4 CHANNELS	COMPRESSION PLUG BNC-W/3773-MTC RG59 YAP METACON
		
	118.76 EUR 118.76 EUR	0.75 EUR 0.75 EUR
Connector type	...	BNC Plug
Attachment of connector elements	...	Compression mounting
Application	...	Coaxial cable
Standard	AHD, HD-CVI, PAL, TCP/IP	...
Dielectric diameter	...	max. 3.7 mm
Wire mounting	...	Pressing
Cable diameter	...	max. 7.3 mm
Shield fastening	...	Compression mounting
Watertightness	...	✓
Example of application	...	<ul style="list-style-type: none"> • RG59 • K-60 • YAP
Main features	...	<ul style="list-style-type: none"> • Properly compressed connection is highly resistant to break • Watertightness of connector with cable connection • Very easy and quick assembly • Corrosion resistance • Very low loss in the whole operating band • To crimp use the crimping tool HT-5082R
Maximal total frame rate	<ul style="list-style-type: none"> • AHD / HD-CVI : max. 48 fps @ 1920 x 1080 px, max. 100 fps @ 1280 x 720 px, • CVBS : max. 100 fps @ 960 x 576 px, max. 100 fps @ 704 x 576 px • IP 100 fps @ max. 2592 x 1944 	...
Recording speed adjustment	1 ... 12 fps @ 1920 x 1080 px 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 960 x 576 px for each channel	...

Operation modes	<ul style="list-style-type: none"> • 4 x AHD / HD-CVI @ 1080p or 4 x CVBS @ 960H • 3 x AHD / HD-CVI @ 1080p or 3 x CVBS @ 960H + 1 x IP max. 5 Mpx • 2 x AHD / HD-CVI @ 1080p or 2 x CVBS @ 960H + 2 x IP max. 5 Mpx <p>The recorder allows to combining the AHD / CVI cameras only in pairs</p>	...
Video inputs	4 pcs BNC - AHD / HD-CVI / Composite Video (CVBS)	...
Video outputs	1 pcs HDMI 1 pcs VGA	...
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Image compression method	H.264	...
Number of compression levels	5	...
Image records resolutions	<p>1920 x 1080 1280 x 720 960 x 576 704 x 576 352 x 576 704 x 288 352 x 288 176 x 144</p>	...
Recording modes	Manual, Motion Detection, Schedule	...
Supported hard drives	1 x 6 TB SATA	...
External storage devices backup	Save single frames and whole records from DVR drive to the USB drive	...
Searching and playback the records	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)	...

Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters - PSS application	...
Network protocols	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, IP Filter, PPPoE, FTP, ONVIF	...
Bitrate	max. 65536 kbps (total)	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...
Alarm inputs / outputs	—	...
PTZ control	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 : PELCO-D/P and others	...
Motion Detection	Split the screen into zones 22 x 18 motion zones Very good sensitivity, after motion detection records detected channels only	...
Mouse support	✓	...
IR remote controller in the set	✓	...
Power supply	12 V DC / 2 A (power adapter included)	...
Weight	0.878 kg	0.014 kg
Dimensions	260 x 236 x 47 mm	Ø 15 mm x 39 mm
Supported languages	English, Polish	...
Country of origin	China	...
Manufacturer / Brand	BCS	METACON
Guarantee	2 years	2 years