





	TV OR MONITOR MOUNT BRATECK-FS22-44TP	MECHANICAL SPLICE SM-1	CONTACTS CLEANING PREPARATION KONTAKT- S/400 SPRAY 400 ml AG TERMOPASTY	PRODUCT FOR CLEANING PRINTING MECHANISMS PRINTER-CLEANER/400 SPRAY 400 ml AG TERMOPASTY
				
	188.05 PLN 188.05 PLN	20.00 PLN 20.00 PLN	27.86 PLN 27.86 PLN	28.42 PLN 28.42 PLN
Fiber positioning	...	based on coating geometry
Support	...	Fujikura Universal Mechanical Splice mechanical splicer from SSM-1 kit
Package	Spray 400 ml	Spray 400 ml
Coating type	...	250 µm, 900 µm
Application	Cleaning and regeneration of contacts	<ul style="list-style-type: none"> • Cleaning the mechanical components of printers (including paper feeding mechanisms, print head drives) • Cleaning heads in dot matrix printers
Mounting standard	VESA : 100 x 100, 200 x 100, 200 x 200, 300 x 200, 300 x 300, 400 x 200 400 x 300, 400 x 400
Screen size range	32 " ... 55 "
Bearing capacity	35 kg
Color	Black
Tilt adjustment	-10 ° ... 10 °
Horizontal rotation	—
Rotation in the plane of the screen	—
Main features	Adjustable shelf height in the range of 60 cm	Splice is suitable for single- and multi-mode fibers	Spray preparation with a brush for easy application in hard-to-reach places	Spray formulation with a straw for easy application in hard-to-reach places
Weight	12 kg	...	0.36 kg	0.35 kg
Dimensions	1170 ... 1470 x 600 x 400 mm	...	Ø 66 x 187 mm	Ø 66 x 200 mm
Manufacturer / Brand	BRATECK	...	AG TERMOPASTY	AG TERMOPASTY
Guarantee	2 years	2 years