

	CRIMP PLUG FME-W/ZAC.H-155	INDUSTRIAL POE SWITCH PFS3228-24GT-360-V2 24-PORT SFP DAHUA	CABLES TESTER UT-681L UNI-T
			
	0.89 EUR 0.89 EUR	336.14 EUR 336.14 EUR	8.10 EUR 8.10 EUR
Connector type	FME Plug
Attachment of connector elements	Crimping
Shield fastening	Crimping
Tested cables	UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C)
Wire mounting	Soldering
Application	Coaxial cable
Cable diameter	max. 6.1 mm
Impedance	50 Ω
Material	Metal
Example of application	<ul style="list-style-type: none"> • TRI-LAN/100 • H-155
LAN ports	...	<ul style="list-style-type: none"> • 24 x RJ45 (2 Hi-PoE (802.3bt) + 22 PoE (802.3af/at) - 10/100/1000 Base-T), • 2 x Uplink (RJ45 - 10/100/1000 Base-T), • 2 x Uplink (port SFP - 1000 Base-X) 	...
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 24 x LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 x Uplink ports, • 1000 Mbps - 2 x SFP ports 	...
Management	...	—	...
Maximal output power	...	<ul style="list-style-type: none"> • 30 W / port PoE • 90 W / port Hi-PoE 	...
Maximal total power	...	360 W	...
MAC addresses table	...	8k	...
Main features	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C 	protection against lightning discharges and voltage differences and strokes between devices	<ul style="list-style-type: none"> • Test for the presence of a short circuit, open circuit • Fast / slow measurement mode • Automatic shutdown after 10 minutes of inactivity • Low battery level alarm

LED diodes	...	Power, Link/Act, PoE, System	...
Certificates	...	CE	...
Power supply	...	100 ... 240 V AC	9V, type 6F22 battery (included)
Operation temp	...	-10 °C ... 55 °C	...
Weight	0.006 kg	3.44 kg	0.17 kg
Dimensions	...	440 x 300 x 44 mm	103 x 96 x 28 mm
Manufacturer / Brand	...	DAHUA	UNI-T
Guarantee	2 years	5 years	2 years