



	SWITCH POE IP-9-11-L2 8-PORT ATTE	WI-FI SMART PLUG ATLO-P1U2-EWELINK Wi-Fi, eWeLink
		
	190.87 USD 190.87 USD	11.12 USD 11.12 USD
Rated voltage	...	100 ... 240 V
Maximal total load	...	3680 W
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE 	...
Total maximal current	...	<ul style="list-style-type: none"> • 16 A @ 230 V AC • 2 x 1 A @ 5 V DC
Management	—	...
LED diodes	Power, LAN	...
Number of outlets	...	<ul style="list-style-type: none"> • 1 pcs - 230 V AC, • 2 pcs - 5 V DC USB
Transmission speed	10 / 100 Mbps : 1 Port LAN + 9 LAN & PoE ports	...
Socket type	...	<ul style="list-style-type: none"> • CEE 7/3 (Schuko), • 2 x USB-A
Plug type	...	CEE 7/7
Grounding	...	✓
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Mobile phones support	...	<ul style="list-style-type: none"> • Android: Free application eWeLink • iOS (iPhone): Free application eWeLink
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports 	...
Maximal total power	96 W	...
Housing	...	Plastic
Color	...	White
Operation temp	...	-20 °C ... 50 °C
Permissible relative humidity	...	≥ 80 %

Operation modes	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5 	...
Main features	<ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices • The output PoE voltage is equal to the input voltage • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement 	<ul style="list-style-type: none"> • schedule, • timer, • remote access, • voice control • Easy operation • ON/OFF button • STATUS indicator
Power supply	230 V AC - cable terminals	...
Weight	1.05 kg	0.13 kg
Dimensions	248 x 222 x 96 mm	122 x 52 x 72 mm
Manufacturer / Brand	ATTE	ATLO
Guarantee	3 years	2 years