

	<a href="#">SMART LED LIGHTING CONTROLLER ATLO-SW1-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">LED LIGHTING CONTROLLER LED-RGBW: WC/RF2 2.4 GHz, RGBW 12 ... 24 V DC MiBOXER / Mi-Light</a>	<a href="#">CONNECTOR FOR LED STRIPS UQS-COB-8W-CS 8 mm</a>	<a href="#">CONNECTOR FOR LED STRIPS AD-TL-6499/Z/L/RGB 10 mm ORNO</a>	<a href="#">WORK GLOVES WG-422/XL Bee-Smart WONDER GRIP</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-ECO-PLUS (6 OUTLETS)</a>
	11.71 AUD 11.71 AUD	17.66 AUD 17.66 AUD	1.29 AUD 1.29 AUD	1.31 AUD 1.31 AUD	7.62 AUD 7.62 AUD	94.59 AUD 94.59 AUD
Maximal load power	...	...	...	...	...	2300 W
Number of channels	1	...	...	...	...	...
Nominal voltage	...	...	...	...	...	230 V AC / 50 Hz
Strip width	...	...	8 mm	10 mm	...	...
Rated voltage	...	12 ... 24 V DC	...	...	...	...
Fuse	...	...	...	...	...	10 A / 250 V
Length of the cable	...	...	140 mm	...	...	...
Power supply	100 ... 240 V AC, 50 / 60 Hz	...	...	...	...	...
Switch	...	...	...	...	...	two-way
Application	switching devices on/off	Works with LED lighting - (RGBW) 12-24V LED strips	Works with LED lighting - COB LED strips	Works with LED lighting RGB	<ul style="list-style-type: none"> <li>• Construction and public works,</li> <li>• Warehousing - packing and logistics,</li> <li>• DIY,</li> <li>• Assembly</li> </ul>	...
Leak current	...	...	...	...	...	< 0.5 mA
Maximal power voltage	...	...	...	48 V	...	...
Response time	...	...	...	...	...	< 25 ns
Nominal voltage of surge suppressor	...	...	...	...	...	250 V
Maximal total load	250 W	<ul style="list-style-type: none"> <li>• 144 W @ 12 V,</li> <li>• 288 W @ 24 V</li> </ul>	...	...	...	...
Protection level	...	...	...	...	...	1.3 kV (L/N)
Material	...	...	...	...	Polyester + latex coating (palm coated)	...
Nominal stroke current	...	...	...	...	...	2 kA (L/N) - (8/20µs)
Total maximal current	10 A	6 A / Channel, 12 A (total)	...	...	...	...
Number of inputs	1	1	...	...	...	...
Maximum stroke current	...	...	...	...	...	6.5 kA (L/N) - (8/20µs)
Number of outputs	1	4 (power)	...	...	...	...
Electric shock protection system	...	...	...	...	...	Ground connectors (pins) connected with ground wire of AC mains
Radio communication range	< 100 m (open area)	...	...	...	...	...
Number of output outlets	...	...	...	...	...	<ul style="list-style-type: none"> <li>• 1 MASTER outlet, two-contact with ground contact</li> <li>• 3 SLAVE outlets with auto switch off the power supply after switch off the receiver powered from MASTER outlet</li> <li>• 2 outlets separate from MASTER outlet</li> </ul>
Connector type	screw terminals	<ul style="list-style-type: none"> <li>• screw terminals,</li> <li>• 5.5/2.1 socket / screw terminals - power input</li> </ul>	...	...	...	...
Length of the cable	...	...	...	...	...	1.45 m
Wireless	<ul style="list-style-type: none"> <li>• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n</li> <li>• Bluetooth</li> </ul>	2.4 GHz	...	...	...	...
Radio communication range (at open area)	...	30 m	...	...	...	...
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	---	...	...	...	...
Supported norms	...	...	...	...	<ul style="list-style-type: none"> <li>• EN 388:2016 - Mechanical protection 3131X</li> <li>• EN 407:2004 - Thermal protection X1XXXX</li> </ul>	...
Size	...	...	...	...	10 / XL	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> <li>Local control by physical button ,</li> <li>Tuya Smart :</li> <li>schedule,</li> <li>timer,</li> <li>Setting scenarios by different events,</li> <li>remote access,</li> <li>voice control ,</li> </ul>	The repeater function allows you to transfer control to subsequent LED-W-WC / LED-RGB-WC / LED-RGBW-WC modules even beyond the direct range of the remote control	...	...	<ul style="list-style-type: none"> <li>Thermal protection : 100 °C ( X1XXXX ),</li> <li>Ergonomics and comfort</li> <li>High grip</li> <li>Soft coating</li> </ul>	...
Housing	Plastic	Plastic	Plastic	...	...	Plastic - non-flammable
"Index of Protection"	IP20	...	—	—	...	...
Color	White	White	Transparent	White	Black + Blue	...
Manufacturer / Brand	...	MiBOXER / Mi-Light	MW Lighting	ORNO	WONDER GRIP	...
Operation temp	-10 °C ... 40 °C	-10 °C ... 40 °C	...	...	...	...
Weight	0.03 kg	0.03 kg	0.002 kg	0.002 kg	...	0.56 kg
Dimensions	43 x 39 x 22 mm	75 x 36 x 17 mm	12 x 10 x 5 mm	20 x 20 mm	...	447 x 55 x 53 mm
Guarantee	2 years	2 years	2 years	2 years	...	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00