



	<a href="#">AHD MOBILE CAMERA ATE-CAM-AHD735HD - 1080p 2.8 mm AUTONE</a>	<a href="#">WLAN USB ADAPTER ARCHER-T4U-PLUS 400 Mbps @ 2.4 GHz, 867 Mbps @ 5 GHz TP-LINK</a>
		
	43.46 EUR 43.46 EUR	29.68 EUR 29.68 EUR
Standard	AHD	...
Sensor	1/3 " Sony CMOS IMX323	...
Matrix size	2.1 Mpx	...
Supported standards	...	IEEE 802.11 b/g/n @ 2.4 GHz, IEEE 802.11 a/n/ac @ 5 GHz
Resolution	1920 x 1080 - 1080p	...
Lens	2.8 mm	...
Supported transmission speeds	...	400 Mbps @ 2.4 GHz , 867 Mbps @ 5 GHz
View angle	91 ° (manufacturer data) 90 ° (our tests result)	...
Operation modes	...	Infrastructure
Range of IR illumination	10 m	...
S/N ratio	≥ 58 dB	...
Antenna type	...	2 x Omnidirectional antenna 5 dBi - Outdoor, Integrated
Interface	...	USB 3.0
Video output	1 Vpp / 75 Ω - M12, 4-pin socket, Code A	...
Frequency range	...	• 2.4 GHz • 5 GHz
Audio	—	...
Transmitter power	...	• 18 dBm @ 2.4 GHz, • 20 dBm @ 5 GHz
Main features	<ul style="list-style-type: none"> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• ICR filter - IR illuminators support</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
OSD menu	—	...
Housing	Dome, Metal	...
Vandal-proof	—	...
Color	Black	...

Application	The camera is designed for installation outside vehicles	...
Power supply	12 V DC / 420 mA - Powering the cameras with 12V DC voltage directly from recorder	...
Power consumption	< 5 W	...
Operation temp	-20 °C ... 60 °C	...
Receiver sensitivity	...	5 GHz <ul style="list-style-type: none"> <li>• 11a 54M : -77 dBm</li> <li>• 11n HT20 : -74 dBm</li> <li>• 11n HT40 : -71 dBm</li> <li>• 11ac VHT20 : -69 dBm</li> <li>• 11ac VHT40 : -65 dBm</li> <li>• 11ac VHT80 : -62 dBm</li> </ul> 2.4 GHz <ul style="list-style-type: none"> <li>• 11b 11M : -87 dBm</li> <li>• 11g 54M : -75 dBm</li> <li>• 11n HT20 : -72 dBm</li> <li>• 11n HT40 : -70 dBm</li> </ul>
Security measures	...	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Main features	...	<ul style="list-style-type: none"> <li>• STATUS indicator</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> </ul>
Included drivers	...	Windows 7 / 8 / 8.1 / 10 / 11, Mac OS < 10.15
Certificates	...	CE, FCC, RoHS
Operation temp	...	0 °C ... 40 °C
Weight	0.27 kg	0.06 kg
Dimensions	90 x 77 x 65 mm	<ul style="list-style-type: none"> <li>• 156 x 84 x 19 mm</li> <li>• Length of the cable : 100 cm</li> </ul>
Manufacturer / Brand	AUTONE	TP-LINK
Guarantee	2 years	3 years