



	<a href="#">RJ-45 PLUG INTERNAL SHIELD RJ45/WP-G/IN</a>	<a href="#">ACCESS POINT 4G LTE +ROUTER ATE-G1CH 150Mb/s AUTONE</a>
		
	0.03 GBP 0.03 GBP	74.56 GBP 74.56 GBP
Frequency range	...	2.4 GHz
Application	RJ-45 modular plug internal shield	...
Material	Plastic	...
Color	Green	...
Antenna type	...	<ul style="list-style-type: none"> <li>• Omnidirectional antenna Wi-Fi - 5 dBi,</li> <li>• 2 x Omnidirectional antenna 4G LTE</li> </ul>
Standards	...	IEEE 802.11 b/g/n, 4G LTE, 3G
Baud rates	...	11n : 150 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 50 Mbps
LAN ports	...	1 x 10/100 Mbps - LAN
Network type	...	<ul style="list-style-type: none"> <li>• 4G : FDD-LTE, WCDMA/HSPA+ B1/B3/B5/B7/B8/B20 - 2100 / 1800 / 2600 / 900 / 800 / 700 MHz</li> <li>• 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz</li> <li>• 3G : UMTS/HSPA+ - 2100 / 900 MHz</li> </ul>
LTE	...	✓
QSS	...	—
WDS	...	—
DHCP server	...	✓
Protections	...	<ul style="list-style-type: none"> <li>• WPA-PSK/WPA2-PSK</li> <li>• SSID hiding</li> <li>• MAC addresses filtering</li> </ul>
Management interface	...	Web browser

Main features	...	<ul style="list-style-type: none"> <li>• SIM socket</li> <li>• DHCP client/server support</li> <li>• DHCP client list</li> <li>• Static routing</li> <li>• Default address : 192.168.100.1</li> </ul>
Power supply	...	12 V DC / 2 A (power adapter included)
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
"Index of Protection"	...	IP66
Weight	0.0005 kg	0.16 kg
Dimensions	20.3 x 11.7 x 7.9 mm	132 x 132 x 50 mm
Manufacturer / Brand	...	AUTONE
Guarantee	2 years	2 years