





	<a href="#">RFID PROXIMITY CARD ATLO-307 13.56 MHz S50</a>	<a href="#">SWITCH POE IP-8-20-L2 8-PORT ATTE</a>	<a href="#">IP CAMERA IPC-F22P-D Wi-Fi BULLET 2C-D - 1080p 2.8 mm IMOU</a>	<a href="#">CABLE N-W/N-W+RF5-10M</a>
				
	0.48 EUR 0.48 EUR	244.95 EUR 244.95 EUR	37.03 EUR 37.03 EUR	20.45 EUR 20.45 EUR
Standard	13.56 MHz S50	...	...	...
Standard	...	...	TCP/IP	...
Compatibility	ISO/IEC 14443A	...	...	...
Sensor	...	...	1/2.8 " Progressive Scan CMOS	...
Possibility of programming the serial number (ID)	—	...	...	...
Matrix size	...	...	2.1 Mpx	...
Ability to write to internal memory	1 kB	...	...	...
Serial Number overprint	—	...	...	...
Resolution	...	...	1920 x 1080 - 1080p	...
Cable	...	...	...	RF-5 : "N" Plug / "N" Plug
Impedance	...	...	...	50 Ω
Lens	...	...	2.8 mm	...
Length of the cable	...	...	...	10 m
View angle	...	...	102 °	...
LAN ports	...	• 2 x RJ45 10/100/1000 Base-TX - Uplink, • 8 x RJ45 10/100 Base-TX + PoE (802.3af/at) / Passive PoE	...	...
Range of IR illumination	...	...	30 m	...
Management	...	—	...	...
Audio	...	...	• Microphone built-in, • Audio transmission via network	...
LED diodes	...	Power, LAN	...	...
Image compression method	...	...	H.265 / H.264	...
Main stream frame rate	...	...	25 fps @ 1080p	...
Network protocols	...	...	TCP, DHCP	...
Transmission speed	...	• 10 / 100 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 LAN ports	...	...
ONVIF	...	...	✓	...
Network interface	...	...	• Ethernet : 100 Mbps • Wi-Fi IEEE 802.11 b/g/n - 2.4 GHz	...
WEB Server	...	...	—	...

Mobile phones support	...	...	Access by a cloud (P2P) • Android: Free application <a href="#">IMOU</a> • iOS (iPhone): Free application <a href="#">IMOU</a>	...
Default admin user / password	...	...	admin / - The administrator password should be set at the first start	...
Maximal output power	...	• 40 W @ Passive PoE - 1 ... 8 ports, • 30 W @ PoE (802.3at) - 1 ... 8 ports, • 15.4 W @ PoE (802.3af) - 1 ... 8 ports	...	...
Default IP address	...	...	DHCP	...
Maximal total power	...	96 W	...	...
Web browser access ports	...	...	—	...
PC client access ports	...	...	—	...
Mobile client access ports	...	...	—	...
Port ONVIF	...	...	—	...
RTSP URL	...	...	—	...
Memory card slot	...	...	Micro SD memory cards up to 256GB support (possible local recording)	...
Main features	...	...	• Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area) • Motion Detection • People detection • D-ZOOM - Digital Zoom : 16x	...
Power consumption	...	...	< 3.5 W	...



Main features	Range : ~ 10 cm ,	<ul style="list-style-type: none"> <li>• Supported PoE devices: 802.3af/at, Passive PoE</li> <li>• Possibility to connecting in cascade @ 90 W</li> <li>• Built-in switching power supply : 48 V DC / 96 W</li> <li>• Efficiency : 92 %</li> <li>• PSU thermal protection</li> <li>• Short-circuit protection</li> <li>• Overload protection</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports</li> <li>• Electronic fuse independently for each PoE channel</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement</li> <li>• "Index of Protection" : IP56</li> </ul>	...	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Corrosion resistance</li> </ul>
"Index of Protection"	...	...	IP67	...
Power supply	...	• 190 ... 260 V AC - Built-in APS-90-480-OF switching mode power supply	12 V DC / 0.5 A (power adapter included)	...
Weight	0.005 kg	1.04 kg	0.24 kg	0.38 kg
Supported languages	...	...	—	...
Dimensions	86 x 54 x 0.8 mm	248 x 198 x 96 mm	148 x 74 x 74 mm	...
Manufacturer / Brand	ATLO	ATTE	DAHUA / IMOU	...
Guarantee	2 years	3 years	2 years	2 years