

	KEYSTONE CONNECTOR FX-USB/C	SWITCHING ADAPTER DRL-24V240W-1EN LYTE II Delta Electronics	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500TLM-IL- A-0280B-S2 - 5 Mpx 2.8 mm DAHUA
			
	1.72 AUD 1.72 AUD	110.94 AUD 110.94 AUD	149.89 AUD 149.89 AUD
Adapter type	...	Switching	...
Power voltage	...	90 ... 264 V AC	...
Output voltage	...	24 V DC	...
Standard	AHD, HD-CVI, HD-TVI, CVBS
Connector type	Adapter USB Socket / USB Socket
Application	Patch panel Keystone
Output voltage adjustment	...	21.6 ... 26.4 V DC	...
Maximal load	...	10 A	...
Material	Metal / PET
Output power	...	240 W	...
Number of outputs	...	2 pcs	...
Main features	<ul style="list-style-type: none"> • Very easy and quick assembly • Keystone assembly standard
Efficiency	...	90 %	...
Housing type	...	DIN	...
Protections	...	<ul style="list-style-type: none"> • Short-circuit • Overload • Overvoltage • Temperature 	...
Operation temp. / Relative humidity	...	-40 °C ... 70 °C / 20 ... 95 %	...
Resolution	2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9 , 2560 x 1440 - 4 Mpx @ HD-CVI / HD-TVI / AHD @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Sensor	Progressive Scan CMOS
Lens	2.8 mm
View angle	106 °
Range of IR illumination	40 m
White light LED illuminator range	40 m

IR illuminator power adjustment	Automatic
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only
OSD menu	✓
Main features	<ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines
Power supply	12 V DC / 380 mA
Power consumption	≤ 4.5 W
Housing	Compact Plastic + Metal
Color	White + Black
"Index of Protection"	IP67
Mechanical protection class	—
Operation temp	-40 °C ... 60 °C
Weight	0.006 kg	0.62 kg	0.3 kg
Dimensions	18 x 22 x 21 mm (W x H x D)	123.6 x 116.8 x 40 mm	198 x 80 x 76 mm
Manufacturer / Brand	...	Delta Electronics	DAHUA
Guarantee	2 years	3 years	3 years