







| | DOME CAMERA BRACKET PFB204W DAHUA | EXTENDER HDMI-EX-120- V4 | BATTERY DS-2FSCH30 FOR THE DS-2XS6A87G1- L/C32S80 CAMERA 10.8 V Hikvision | MOUNTING RAIL DIN TS-35 OMI-5-DIN FOR OMI-5 ENCLOSURE SATEL | OUTDOOR IR ILLUMINATOR IRL-30/120 | STABILIZER 24V/12V DC RV-16 |
|--|---|---|--|---|---|---|
| |  |  |  |  |  |  |
| | 293.87 NOK 293.87 NOK | 1428.49 NOK 1428.49 NOK | 12169.05 NOK 12169.05 NOK | 277.08 NOK 277.08 NOK | 353.76 NOK 353.76 NOK | 137.03 NOK 137.03 NOK |
| Rated voltage | ... | ... | 10.8 V | ... | ... | ... |
| Type | ... | ... | ... | ... | ... | Decreasing the voltage |
| Range | ... | ... | ... | ... | 30 m | ... |
| Suitable for cameras | DAHUA - documentation for download below. | ... | ... | ... | ... | ... |
| Length | ... | ... | ... | 281 mm | ... | ... |
| Battery capacity | ... | ... | 30 Ah | ... | ... | ... |
| Illumination angle | ... | ... | ... | ... | 120 ° | ... |
| Material | Aluminum | ... | ... | ... | ... | ... |
| Material | ... | ... | ... | Steel galvanized | ... | ... |
| Power voltage | ... | ... | ... | ... | ... | 15 V ... 28 V DC |
| Application | ... | ... | DS-2XS6A87G1-L/C32S80 | ... | ... | ... |
| Output voltage | ... | ... | ... | ... | ... | 13.8 V AC |
| Twilight switch | ... | ... | ... | ... | ✓ | ... |
| Output voltage adjustment | ... | ... | ... | ... | ... | — |
| Battery charging voltage | ... | ... | max. 12.6 V | ... | ... | ... |
| Maximal output current | ... | ... | 8 A | ... | ... | 4 A (continuous operation) |
| Supported HDMI resolutions | ... | 480i, 576i, 480p, 576p, 720p, 1080p | ... | ... | ... | ... |
| Optical wavelength | ... | ... | ... | ... | 850 nm | ... |
| Main features | ... | ... | • Built-in MPPT batteries solar charge controller • RS-485 control | • Dedicated for mounting in the OMI-5 enclosure, • Mounting brackets included in the set | ... | ... |
| Housing | ... | ... | Aluminum | ... | Aluminum | ... |
| Protections | ... | ... | ... | ... | ... | • Short-circuit • Overload • Overheat |
| Maximal transmission range | ... | 100 m UTP cat. 5e 120 m UTP cat. 6 | ... | ... | ... | ... |
| "Index of Protection" | ... | ... | IP68 | ... | IP65 | ... |
| Max. number of receivers working in the same time | ... | 237 | ... | ... | ... | ... |
| Color | White | ... | White | ... | ... | ... |
| Protocols | ... | HDbiT | ... | ... | ... | ... |
| Supported HDMI standard | ... | 1.3 | ... | ... | ... | ... |
| HDCP | ... | 1.4 | ... | ... | ... | ... |
| Type (size) | ... | ... | 255 x 172 x 80 mm | ... | ... | ... |
| Operation temp | ... | 0 °C ... 60 °C | ... | ... | -20 °C ... 70 °C | ... |
| Manufacturer / Brand | DAHUA | ... | Hikvision | SATEL | ... | ... |
| Permissible relative humidity | ... | 10 % ... 90 % (non- condensing) | ... | ... | ... | ... |
| Power supply | ... | 5 V DC / 1 A (power adapter included) | ... | ... | 12 V DC / 1.67 A | ... |
| Dimensions | 122 x 160 x 76 mm | 110 x 58 x 26 mm | ... | 281 x 35 x 43 mm | 180 x 140 x 94 | 165 x 74 x 31 mm |
| Weight | 0.506 kg | 0.13 kg | 3.4 kg | 0.17 kg | 0.75 kg | 0.315 kg |
| Guarantee | 3 years | 2 years | 2 years | 2 years | 2 years | 2 years |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00