

	SWITCH POE DS-3E0326P-E/M(B) 24-PORT SFP Hikvision	IP CAMERA IPC2124LB-SF40KM-G - 3.7 Mpx 4 mm UNIVIEW
		
	350.78 EUR 350.78 EUR	156.84 EUR 156.84 EUR
Standard	...	TCP/IP
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	4 Mpx
LAN ports	<ul style="list-style-type: none"> • 24 x RJ45 10/100 Base-TX (24 x PoE (802.3af/at)), • 1 x port SFP - Uplink, • 1 x RJ45 - Uplink 	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	4 mm
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 Mbps - 24 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports 	...
Maximal output power	30 W / port PoE	...
Maximal total power	230 W	...
MAC addresses table	4k	...
View angle	...	<ul style="list-style-type: none"> • 79 ° (manufacturer data) • 76 ° (our tests result)
Management	—	...
Range of IR illumination	...	30 m
S/N ratio	...	> 56 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	—
Main stream frame rate	...	25 fps @ 3.7 Mpx

Main features	<ul style="list-style-type: none"> • Extend - 17 ... 24 ports : 300 m, 10 Mbps @ UTP cat. 5e, 6 • Support of the 3 network modes: Priority, Standard, Extend • protection against lightning discharges and voltage differences and strokes between devices • High priority ports : 1 ... 8 ports - Dedicated to video transmission • PoE power mode : The device supports 8-pin power supply 	...
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
LED diodes	Power, Link/Act, PoE, G1, G2, PoE Max	...
Certificates	CE	...
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Operation temp	-10 °C ... 55 °C	...
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
SAP Code	301801300	...
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream

Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion Detection - max. 4 zones • Sharpness - sharper image outlines • Intelligent image analysis : crossing the line (tripwire), intrusion
Power supply	100 ... 240 V AC	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 460 mA
Power consumption	...	≤ 5.5 W
Housing	...	Compact, Metal + Plastic
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	2.54 kg	0.48 kg
Dimensions	335 x 226 x 45 mm	165 x 63 x 63 mm
Supported languages	...	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	Hikvision	UNIVIEW
Guarantee	3 years	3 years