



| | | |
|-------------------------------------|---|---|
| | POLE MOUNT DS-1475ZJ-SUS Hikvision | TIME & ATTENDANCE RECORDER ASA3213G-MW DAHUA |
| |  |  |
| | 55.05 EUR 55.05 EUR | 480.77 EUR 480.77 EUR |
| Suitable for cameras | Hikvision | ... |
| Sensor | ... | CMOS |
| Matrix size | ... | 2 Mpx |
| Pole diameters range | Ø 67 ... Ø 127 mm | ... |
| Material | Stainless steel | ... |
| Resolution | ... | 1920 x 1080 - 1080p |
| SAP Code | 302701860 | ... |
| Standard | ... | TCP/IP |
| IR illuminator | ... | ✓ |
| LED illuminator | ... | ✓ |
| Temperature measurement | ... | — |
| Temperature measurement range | ... | — |
| Accuracy of temperature measurement | ... | — |
| Face recognition distance | ... | 0.3 m ... 1.5 m (max 500 faces in the database) |
| RFID proximity reader built-in | ... | <ul style="list-style-type: none"> • 13.56 MHz S50 • Memory of 500 RFID cards |
| Internal memory | ... | Support storage of 150 000 records |
| Video output | ... | — |
| RS-485 interface | ... | ✓ |
| RS-232 interface | ... | — |
| Wiegand interface | ... | — |
| USB | ... | 1 x USB 2.0 |
| Memory card slot | ... | — |
| Alarm inputs / outputs | ... | 1 / 1 - Relay outputs |
| Audio | ... | Voice message |
| Network interface | ... | 1 x 10/100 Base-T (RJ-45) |
| Network protocols | ... | IPv4, RTSP, RTP, TCP, UDP, P2P |
| WEB Server | ... | Built-in |
| ONVIF | ... | — |
| Default IP address | ... | 192.168.1.108 |

| | | |
|-------------------------------|-------------------|---|
| Default admin user / password | ... | admin / - The administrator password should be set at the first start |
| Web browser access ports | ... | 80, 37777 |
| PC client access ports | ... | 37777 |
| Main features | ... | <ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • 500 users • Software update via network • Real-time Surveillance • Multiple Authentication • Take face image after swiping card • Auto-Registration • Recording of information about Time&Attendance • Statistical Reporting • Backup to USB drive (pendrive, external drive) • Output button support • Door status detection • Lock control • Tamper protections |
| Power supply | ... | 12 V DC / 1.5 A (power adapter included) |
| Power consumption | ... | ≤ 18 W |
| Housing | ... | Plastic (ABS) |
| Color | White | Black + Silver |
| "Index of Protection" | ... | — |
| Operation temp | ... | -10 °C ... 55 °C |
| Weight | 1.23 kg | <ul style="list-style-type: none"> • 0.22 kg (without stand) • 0.24 kg (with stand) |
| Dimensions | 127 x 250 x 46 mm | <ul style="list-style-type: none"> • 116 x 107 x 22 mm (without stand) • 116 x 107 x 78 mm (with stand) |
| Supported languages | ... | English |
| Manufacturer / Brand | Hikvision | DAHUA |

| | | |
|-----------|---------|---------|
| Guarantee | 3 years | 3 years |
|-----------|---------|---------|



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00