

	SPLITTER RI-2/1F-SAT-SIG	DUAL SMART LED LIGHTING CONTROLLER ATLO-SW2-TUYA Wi-Fi, Tuya Smart	POWER DISTRIBUTION UNIT LE-049480 (3 OUTLETS) 1.5 m LEGRAND	EXTENSION CORD WITH GROUNDING PS-3X1.5-Z/10M 10 m	USB SWITCH US-221A ATEN	POWER DISTRIBUTION UNIT LE-049475 (4 OUTLETS) 1.5 m LEGRAND	EXTENSION CABLE PS-2X1.5-30M/ORANGE 30 m
							
	3.90 AUD 3.90 AUD	18.27 AUD 18.27 AUD	24.18 AUD 24.18 AUD	16.33 AUD 16.33 AUD	57.96 AUD 57.96 AUD	20.11 AUD 20.11 AUD	31.84 AUD 31.84 AUD
Application	...	switching devices on/off
Number of channels	...	2
Rated voltage	230 V AC / 50 Hz	230 V AC / 50 Hz	...	230 V AC / 50 Hz	230 V AC / 50 Hz
Frequency range	5 ... 2300 MHz
Attenuation	6 dB
Connectors	• 2 x socket USB 2.0 B - Computer interface • 1 x socket USB 2.0 A - Connecting to the device
Power supply	...	100 ... 240 V AC, 50 / 60 Hz
Isolation between outputs	16 dB
Length of the cable	180 cm
Maximal total load	...	2 x 150 W	3680 W	3680 W	...	3680 W	2500 W
Number of outlets	5 grounded outlets 16A/250V CEE 7/5	1 CEE 7/5	...	4 grounded outlets 16A/250V CEE 7/5	1 x CEE 7/17
Possibility to pass the DC voltage to the preamplifier	✓
USB standard	2.0
Total maximal current	...	2 x 5 A	16 A	16 A	...	16 A	10 A
Fuse	—	—	...	—	—
Shielding	✓
Switch	—	—	...	—	—
Wire gauge	3 x 1.0 mm ²	3 x 1.5 mm ²	...	3 x 1.0 mm ²	2 x 1.5 mm ²
Number of inputs	1 pcs	2
Impedance	75 Ω
Length of the cable	1.5 m	10 m	...	1.5 m	30 m
Number of outputs	2 pcs	2
Connector type	...	screw terminals
Wireless	...	• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n • Bluetooth
Radio communication range	...	< 100 m (open area)
Manufacturer / Brand	LEGRAND	...	ATEN	LEGRAND	...
Mobile phones support	...	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Main features	...	• Local control by physical button , Tuya Smart : • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control ,	• LED indication • Support for platforms: Windows, Linux, Mac, Sun • Overload protection • USB A / USB B cable included - 1.8 m
Housing	...	Plastic	Plastic	Plastic	...
"Index of Protection"	...	IP20
Color	...	White	White / Gray	Orange	...	White / Light gray	Orange
Operation temp	...	-10 °C ... 40 °C
Weight	0.09 kg	0.03 kg	0.36 kg	4.1 kg	0.05 kg	0.33 kg	2.3 kg
Dimensions	60 x 50 x 25 mm	43 x 39 x 22 mm	253 x 54 x 37 mm	...	72 x 66 x 25 mm	208 x 53 x 38 mm	...
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00