


	SHUNT TRIP LE-406278 FOR THE LEGRAND DEVICES OF THE TX3, DX3, FR300, FRX300, FRX400 SERIES LEGRAND	TWILIGHT SWITCH FOR LED LIGHTING TWILIGHT-COMPACT/BLEBOX 12 ... 24 V DC	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH-2WIRE-A-SET 2 PCS SET ATTE
			
	773.97 CZK 773.97 CZK	382.49 CZK 382.49 CZK	2793.33 CZK 2793.33 CZK
Device type	Shunt trip
PTZ control	The appearance of voltage
Application	...	Works with LED lighting - 12-24V LED strips	...
Rated voltage	110 V ... 415 V AC	12 ... 24 V DC	...
Connectors type	screw terminals
Maximal total load	...	60 ... 120 W	...
Total maximal current	...	5 A	...
Connectors	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm² (22 ... 12 AWG)
Number of inputs	...	0	...
Width in 17.5 mm modules	1
Number of outputs	...	1	...
LAN ports	1 pcs RJ45 10 / 100 Mbps
Connector type	...	screw terminals	...
Wireless	...	—	...
Mobile phones support	...	—	...
Color	...	Black	...
Terminals	<p>ETH-2WIRE-A-TX :</p> <ul style="list-style-type: none"> • PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W (" +/ -": 1, 2 pins; " +/ -": 3, 6 pins) or (" +/ -": 4, 5 pins; " +/ -": 7, 8 pins) • Power • DATA - 2-wire <p>ETH-2WIRE-A-RX :</p> <ul style="list-style-type: none"> • PoE OUT - Hi-PoE (802.3af/at/bt) (" +": 3, 6 / 4, 5 pins; "-": 1, 2 / 7, 8 pins) • Power • DATA - 2-wire
Transmission speed	10 / 100 Mbps

Transmission range	<ul style="list-style-type: none"> • 300 m @ 100 Mbps : 2-wire, • 800 m @ 10 Mbps : 2-wire • 100 m @ UTP : Switch PoE - ETH-2WIRE-A-TX • 100 m @ UTP : ETH-2WIRE-A-RX - IP Camera
LED indicators	<ul style="list-style-type: none"> • Power • LAN (RJ-45) • PoE (RJ-45) • 2-wire • 2-wire 10 Mbps • LV - low voltage < 44 V
Protections	<ul style="list-style-type: none"> • Overvoltage - LAN, DATA • Protection against reverse polarity connection - Power • Overload 0.6 A - PoE IN ETH-2WIRE-A-TX
Main features	...	<ul style="list-style-type: none"> • High power - max. 120 W, • Automatic calibration, • Mild lightening at dusk, • Mild darkening at dawn, • Small dimensions 	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks
Power supply	<p>ETH-2WIRE-A-TX :</p> <ul style="list-style-type: none"> • 24 ... 56 V DC - PoE • 12 ... 56 V DC - Power <p>ETH-2WIRE-A-RX :</p> <ul style="list-style-type: none"> • 44 ... 56 V - Power • The output PoE voltage is equal to the input voltage
Power consumption	1.35 W (total)
Housing	Plastic, Direct mounting on selected Legrand DIN TS-35 rail mounting units, on the left-hand side of the device	Self-extinguishing	Plastic (polycarbonate)
"Index of Protection"	...	IP20	IP20
Operation temp	...	-20 °C ... 50 °C	-25 °C ... 65 °C
Weight	0.086 kg	0.008 kg	0.028 kg (single element)
Dimensions	18 x 85 x 78 mm	23 x 17 x 22 mm	73 x 51 x 23 mm (single element)
Manufacturer / Brand	LEGRAND	BleBox	ATTE
Guarantee	2 years	2 years	3 years