



	<a href="#">EXTENDER HDMI-EX-30-ECO</a>	<a href="#">OVERVOLTAGE LIMITER AXON-POE/PROF</a>
		
	9.74 EUR 9.74 EUR	41.92 EUR 41.92 EUR
Rated voltage	...	5 V
Maximal voltage	...	6 V
Voltage protection level line-line	...	≤ 40 - 1 kV/μs
Supported HDMI resolutions	480i, 576i, 480p, 576p, 720p, 1080p	...
Maximal transmission range	30 m UTP cat. 5, 5e, 6	...
Voltage protection level line-PG	...	≤ 600 - 1 kV/μs
Nominal discharge current (line-line)	...	20 A (10/1000μs)
Max. number of receivers working in the same time	1	...
Nominal discharge current (line-PG)	...	20 A (10/1000μs)
Supported HDMI standard	1.4	...
Nominal power voltage	...	50 V
Maximal power voltage	...	56 V
Operation temp	0 °C ... 70 °C	...
Nominal current	...	400 mA
Nominal discharge current line-line for power	...	10 A (10/1000μs)
Permissible relative humidity	10 % ... 85 % (non-condensing)	...
Nominal discharge current for power (line-PG)	...	2 kA (8/20μs)
Power supply	—	...
Voltage protection level line-line for power	...	≤ 95 V - 1 kV/μs
Voltage protection level line-PG for power	...	≤ 1000 V - 1 kV/μs
Norm	...	Compliance with PN-EN61643-21
Sockets types	...	RJ45 (8P8C)
Housing	...	Metal, black
Dimensions	58 x 25 x 21 mm	95 x 50 x 30 mm
Weight	0.02 kg	0.18 kg
Guarantee	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00