





	EXTENDER HDMI-EX-6IR	INFRA-RED BARRIERS SATEL ACTIVA-5-BR 5 BEAMS SATEL	EXPANSION PLUG KS-14/10X100 KLIMAS	VIDEO DOORPHONE S1204A VIDOS
				
	51.30 CHF 51.30 CHF	188.96 CHF 188.96 CHF	0.62 CHF 0.62 CHF	167.23 CHF 167.23 CHF
Number of beams	...	5
Compatibility	VIDOS DUO
Detection method	...	Programmable number of beams, which interruption trigger an alarm
Outdoor detection range	...	10 m
Indoor detection range	...	20 m
Material	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized 	...
Sensor	1/2.7 " Fish Eye CMOS, 2 Mpx
Beam characteristics	...	Transmission encoding
Drilling diameter	14 mm	...
View angle	170 °
Expansion plug length	80 mm	...
IR illuminator	—
Interruption time (blocking of the beam)	...	40 ... 1000 ms
Supported HDMI resolutions	1080i - 50/60 Hz, 720p, 576p, 576i, 480p, 480i
LED illuminator	✓
Alarm period	...	2 s
Tamper contact	...	NC
Screw dimensions	Ø 10 x 100 mm, SW-17	...
proximity reader built-in	Standard : Unique EM 125kHz
Assembly	...	Possibility to mount to the wall
The number of subscribers served	4
Video output	compatible with the VIDOS DUO digital video doorphone system
Current consumption	...	max. 45 mA
Maximal transmission range	<ul style="list-style-type: none"> 45 m @ 720p / 1080i - UTP cat. 5 60 m @ 720p / 1080i - UTP cat. 6
Angles adjustment range	...	—
Application	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick Natural stone 	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp. / Relative humidity	...	-25 °C ... 55 °C / max. 95 %
Supported audio formats	DTS-HD, Dolby true HD, LPCM7.1, AC3, DTS, DSD
Main features	...	<ul style="list-style-type: none"> • trimmer sensitivity adjustment • RS-232 port allows to programming using the PC with ACTIVA software installed
Power supply	5 V DC / 1000 mA - 2 pcs of power adapters included	12 V DC	...	24 V DC
Transmitter or receiver dimensions	...	1315 x 25 x 26 mm
Main features	IR receiver : 20 ... 60 kHz	<ul style="list-style-type: none"> • Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 Module • Support up to 12 internal devices - 4 for each premises • PIR detectors support • Permanent or cyclical zoom-up of the observed image • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 300mA • Easy to add and delete users via MASTER key fobs
Transmitter and receiver weight	...	0.618 kg
Power consumption	≤ 3 W (operation) ≤ 0.8 W (Standby mode)
Housing	Acid-proof steel / Plastic, Waterproof
Permissible relative humidity	5 % ... 90 %
Color	...	Brown	...	Silver
"Index of Protection"	...	IP44	...	IP54
Operation temp	-10 °C ... 55 °C	-20 °C ... 55 °C
Weight	0.08 kg	0.72 kg
Dimensions	72 x 67 x 25 mm	220 x 120 x 49 mm
Manufacturer / Brand	...	SATEL	KLIMAS	VIDOS
Guarantee	2 years	2 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00