



	<a href="#">IP CAMERA IPC2124LE-ADF28KMC-WL-BLACK ColorHunter - 4 Mpx 2.8 mm UNIVIEW</a>	<a href="#">IP CAMERA F4C-PV Wi-Fi. Smart Dual Light Active Deterrence - 3.7 Mpx 2.8 mm DAHUA</a>
		
	348.40 AUD 348.40 AUD	73.81 AUD 73.81 AUD
Standard	TCP/IP	IP
Matrix size	4 Mpx	...
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Sensor	1/3 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Lens	2.8 mm	2.8 mm
View angle	• 113 ° (manufacturer data) • 97 ° (our tests result)	98 °
Range of IR illumination	30 m	30 m
White light LED illuminator range	30 m	30 m
S/N ratio	> 52 dB	> 56 dB
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264
Alarm inputs / outputs	—	—
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Speaker built-in</li> <li>• Audio detection</li> <li>• Bi-directional audio streaming support</li> </ul>	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speaker built-in,</li> <li>• Bi-directional audio streaming support</li> <li>• Audio output</li> <li>• Audio detection</li> </ul>
Main stream frame rate	25 fps @ 4 Mpx	25 fps @ 4 Mpx
Network interface	10/100 Base-T (RJ-45)	<ul style="list-style-type: none"> <li>• Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz,</li> <li>• 10/100 Base-T (RJ-45)</li> </ul>
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, SSL / TLS	...
WEB Server	Built-in	Built-in
Max. number of on-line users	32	6
ONVIF	✓	✓
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>
Default IP address	DHCP or 192.168.1.13	192.168.1.108
Default admin user / password	admin / 123456	admin / - The administrator password should be set at the first start
Web browser access ports	80, 554	80, 37777

PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	37777
Mobile client access ports	80	37777
Port ONVIF	80	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette)</li> </ul>	<ul style="list-style-type: none"> <li>• Active deterrence function</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Motion Detection - max. 4 configurable zones - Human detection</li> <li>• Privacy zones - max. 4</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 750 mA</li> </ul>	12 V DC / 550 mA
Power consumption	≤ 9 W	≤ 6.6 W @ 12 V DC
Housing	Compact, Metal + Plastic	Compact - Plastic
Color	Black	White + Black
"Index of Protection"	IP67	IP67
Vandal-proof	—	—
Operation temp	-30 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.42 kg	0.25 kg
Dimensions	191 75 x 74 mm	131 x 78 x 97 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English
Manufacturer / Brand	UNIVIEW	DAHUA
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00