



|                          | <a href="#">ELECTRICAL<br/>INSTALLATION<br/>CONNECTION KZ-37-UV</a>   | <a href="#">ELECTRIC ENERGY METER<br/>OR-WE-521 ONE-PHASE<br/>ORNO</a>   |
|--------------------------|---|--|
|                          |    |    |
|                          | 0.51 EUR<br>0.51 EUR  | 19.84 EUR<br>19.84 EUR   |
| Inner diameter           | Ø 37 mm   | ...  |
| Device type              | ...   | Electric Energy Meter, One-phase   |
| Rated voltage            | ...   | 230 V AC, 50 Hz  |
| Measurement unit         | ...   | kWh  |
| Pipe mounting method     | Pressing  | ...  |
| Color                    | Black   | ...  |
| Current                  | ...   | 5 A - Base current<br>40 A - Max. current  |
| LCD display              | ...   | 5+2 digits ( 00000.00 kWh )  |
| Measuring accuracy       | ...   | 0.001 kWh  |
| Impulse frequency        | ...   | 1000 imp/kWh   |
| RS-485 ports             | ...   | —  |
| Connectors type          | ...   | screw terminals max. 6 mm <sup>2</sup>   |
| Main features            | <ul style="list-style-type: none"> <li>• The corrugation of the connection enables its bend,</li> <li>• Material : PCV,</li> <li>• UV radiation resistance</li> </ul> | <ul style="list-style-type: none"> <li>• Blue backlight</li> <li>• LED indication</li> <li>• Pulse output</li> <li>• The kit includes two clamp seals to protect the meter connectors</li> </ul> |
| Housing                  | ...   | Plastic, DIN, TS-35 rail mounting  |
| "Index of Protection"    | ...   | IP51   |
| Operation temp           | ...   | -25 °C ... 55 °C   |
| Width in 17.5 mm modules | ...   | 1  |
| Weight                   | ...   | 0.07 kg  |
| Dimensions               | Ø 40 x 215 mm   | 60 x 110 x 17.5 mm   |
| Manufacturer / Brand     | ...   | ORNO   |
| Guarantee                | 2 years   | 5 years  |