



	OFFSET ANTENNA AS-90/ALU-CORAB 90cm CORAB	SPEED DOME CAMERAS OVERVOLTAGE LIMITER OPSD-5
		
	71.32 CAD 71.32 CAD	33.83 CAD 33.83 CAD
LNB holder	Ø 40 mm	...
Maximal mast diameter	Ø 60 mm	...
Gain	39.1 dB	...
Material	Aluminum	...
Standard	...	<ul style="list-style-type: none"> • AHD - 5 Mpx • HD-CVI - 8 Mpx 4K UHD • HD-TVI - 5 Mpx • CVBS - PAL / NTSC
Device protects	...	<ul style="list-style-type: none"> • Video line (asymmetric or symmetric signal) • RS-485 • Power supply 12V DC • Power supply 24V AC
Input socket type	...	terminals
Output socket type	...	terminals
Threshold voltage	...	<ul style="list-style-type: none"> > 2.4 V (wire/wire) (Video) > 8.2 V (wire/wire) (RS-485) > 15 V (wire/wire) (Power supply 12V DC) > 36 V (wire/wire) (Power supply 24V AC) > 18.4 V (wire/ground) (Video) > 19.4 V (wire/ground) (RS-485) > 47 V (wire/ground) (Power supply 12V DC) > 47 V (wire/ground) (Power supply 24V AC)
Maximum stroke current	...	<ul style="list-style-type: none"> 5 kA (Video) 5 kA (Power supply 12V DC) 5 kA (Power supply 24V AC)
Maximal stroke current RS-485 (t=8.3ms)	...	30 A
Serial impedance per line	...	1 Ω (Wire Video)
Capacity	...	< 7 pF (Video)

Response time	...	15 ns (Video) 15 ns (RS-485) 15 ns (Power supply 12V DC) 15 ns (Power supply 24V AC)
Operation temp	...	-50 °C ... 55 °C
Permissible relative humidity	...	< 95 %
Weight	4.37 kg	0.11 kg
Dimensions	960 x 860 mm	120 x 91 x 37 mm
Manufacturer / Brand	CORAB	DELTA
Guarantee	2 years	3 years