









	RFID PROXIMITY CARD ATLO-104N*P50	SILICONE CAMERA COVER FBS10-B-JMGU	MULTIMEDIA SHELF AX- RTV1	WIRED DOORBELL ATLO- DB-1	POE SWITCH / EXTENDER PFT1300 3-PORT DAHUA	RFID PROXIMITY CARD KT- STD-2 SATEL	EXTENDER HDMI+USB- EX-70-4KV2
							
	16.98 EUR 16.98 EUR	8.40 EUR 8.40 EUR	9.65 EUR 9.65 EUR	4.07 EUR 4.07 EUR	23.53 EUR 23.53 EUR	1.94 EUR 1.94 EUR	178.15 EUR 178.15 EUR
Number of shelves	...	...	1	...	...	...	...
Material	...	Silicon	...	...	...	...	...
Listen to the available sounds	...	...	...		...	...	...
Bearing capacity	...	...	10 kg	...	...	...	...
Signaling mode	...	...	...	Sound signaling	...	...	...
Supported HDMI resolutions	...	...	...	...	...	...	max. 4K UHD @ 60 Hz
Swivel angle adjustment:	...	...	---	...	...	...	...
Number of ring-tones	...	...	...	1	...	...	...
Color	...	Black	Black	...	...	...	...
In package	<b>50 pcs The price for package</b>	...	...	...	...	...	...
Volume adjustment	...	...	...	---	...	...	...
Distance from mounting surface	...	...	3 mm	...	...	...	...
Standard	Unique EM 125kHz	...	...	...	...	Unique EM 125kHz	...
Compatibility	EM4100/4102	...	...	...	...	EM4100/4102	...
"Index of Protection"	...	...	...	IP40	...	...	...
Possibility of programming the serial number (ID)	---	...	...	...	...	---	...
LAN ports	...	...	...	...	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at),</li> <li>• 2 x RJ45 10/100 Base-T + PoE (802.3af)</li> </ul>	...	...
Ability to write to internal memory	---	...	...	...	...	---	...
Serial Number overprint	✓	...	...	...	...	✓	...
Management	...	...	...	...	---	...	...
LED diodes	...	...	...	...	LAN, PoE	...	...
Transmission speed	...	...	...	...	10 / 100 Mbps	...	...
Maximal transmission range	...	...	...	...	...	...	<ul style="list-style-type: none"> <li>• 60 m - UTP cat. 6, 6A, 7 @ 4K UHD (manufacturer data)</li> <li>• 70 m - UTP cat. 5e @ 1080p (our tests result)</li> <li>• 20 m - UTP cat. 5e @ 4K UHD (our tests result)</li> <li>• 60 m - UTP cat. 6 @ 4K UHD (our tests result)</li> </ul>
Maximal output power	...	...	...	...	<ul style="list-style-type: none"> <li>• 15.4 W @ port PoE - First device</li> <li>• 3 W @ port PoE - Second device in cascade</li> </ul>	...	...
Power consumption	...	...	...	...	0.3 W	...	...
Main features	...	...	...	...	...	...	<ul style="list-style-type: none"> <li>• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse</li> <li>• Support KVM function,</li> <li>• HDR10 support</li> <li>• Transition of the HDMI signal in the transmitter</li> <li>• EDID support</li> <li>• ESD protection</li> </ul>
Range	...	...	...	...	100 m - Input 100 m - Output	...	...
Protections	...	...	...	...	Overvoltage	...	...
Housing	...	...	...	...	Plastic, DIN, TS-35 rail mounting	...	...
Main features	<ul style="list-style-type: none"> <li>• Serial Number Format : 8H10D + WEG24A</li> <li>• Range: ~ 11 cm</li> <li>• The TK-4100 chip</li> </ul>	...	...	...	<ul style="list-style-type: none"> <li>• Possibility to connecting in cascade</li> <li>• The device can function as a LAN network and PoE power extender</li> </ul>	...	<ul style="list-style-type: none"> <li>• Very good image quality with no visible distortions caused by compression,</li> <li>• No delays in video transmission,</li> <li>• No delays in mouse control operations</li> <li>• Designed to continuous operation 24/7</li> </ul>
Operation temp. / Relative humidity	...	...	...	...	-30 ... 65 °C / 10 ... 90 %	...	...
Power supply	...	...	...	12 V DC	PoE (802.3af/at)	...	5 V DC / 1 A - 2 pcs (included)
Operation temp	...	...	...	...	...	...	-20 °C ... 60 °C
Manufacturer / Brand	ATLO	DAHUA	...	ATLO	DAHUA	SATEL	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Permissible relative humidity	...	...	...	...	...	...	0 % ... 90 % (non-condensing)
Weight	0.006 kg	0.03 kg	1.33 kg	0.06 kg	0.06 kg	0.009 kg	0.12 kg
Dimensions	86 x 54 x 1 mm	65 x 78 x 76 mm	300 x 250 x 38 mm	62 x 88 x 24 mm	80 x 51 x 23 mm	86 x 54 x 2 mm	85 x 75 x 20 mm - Transmitter or receiver dimensions
Guarantee	2 years	2 years	2 years	3 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00