



| | | |
|-------------------------------|---|---|
| | IP CAMERA DS-2CD2083G2-I(2.8MM) ACUSENSE - 8.3 Mpx Hikvision | EXPANSION PLUG KS-12/8X100 KLIMAS |
| |  |  |
| | 311.54 EUR 311.54 EUR | 0.42 EUR 0.42 EUR |
| Standard | TCP/IP | ... |
| Sensor | 1/2.8 " Progressive Scan CMOS | ... |
| Matrix size | 8.3 Mpx | ... |
| Material | ... | <ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized |
| Drilling diameter | ... | 12 mm |
| Expansion plug length | ... | 80 mm |
| Screw dimensions | ... | Ø 8 x 100 mm, SW-13 |
| Application | ... | <ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick |
| Resolution | 3840 x 2160 - 8.3 Mpx , 3200 x 1800 - 5 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p | ... |
| Lens | 2.8 mm | ... |
| View angle | 107 ° | ... |
| Compression | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... |
| Range of IR illumination | 40 m | ... |
| Alarm inputs / outputs | — | ... |
| Audio | — | ... |
| Memory card slot | Micro SD memory cards up to 512GB support (possible local recording) | ... |
| Main stream frame rate | 25 fps @ 8.3 Mpx | ... |
| Network interface | 10/100 Base-T (RJ-45) | ... |
| WEB Server | Built-in | ... |
| Max. number of on-line users | 6 | ... |
| ONVIF | ✓ | ... |
| Mobile phones support | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect | ... |
| Default IP address | 192.168.1.64 | ... |
| Default admin user / password | admin / - The administrator password should be set at the first start | ... |
| Web browser access ports | 80 | ... |

| | | |
|----------------------------|--|---------|
| PC client access ports | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application | ... |
| Mobile client access ports | 8000 | ... |
| Port ONVIF | 80 | ... |
| RTSP URL | <ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ | ... |
| RS-485 interface | — | ... |
| Main features | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • ICR - Movable InfraRed filter • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, face detection | ... |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA | ... |
| Power consumption | <ul style="list-style-type: none"> • ≤ 7.2 W @ PoE (802.3af) • ≤ 6 W @ 12 V DC | ... |
| Housing | Compact, Metal | ... |
| Color | White | ... |
| "Index of Protection" | IP67 | ... |
| Operation temp | -30 °C ... 60 °C | ... |
| Supported languages | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian | ... |
| Weight | 0.5 kg | ... |
| Dimensions | Ø 70 x 162 mm | ... |
| Manufacturer / Brand | Hikvision | KLIMAS |
| SAP Code | 311316039 | ... |
| Guarantee | 3 years | 2 years |