









	ACCESS CONTROLLER PR622-G ROGER	TV OR MONITOR MOUNT AX-TYTAN-MAXXIM	TV OR MONITOR MOUNT BBATECK-LP77-44T	MONITOR DESK MOUNT AX-PIXEL-SINGLE RED EAGLE	BATTERY-FREE WIRELESS DOORBELL BUTTON ATLO- DB-2/IX	EXTENDER HDMI+USB; EX-100-4K	ACCESS POINT 4G+ LTE +ROUTER RUT260 2.4 GHz 300 Mbps Teltonika	EXPANSION PLUG JPK-L2X160M5 EBOLT
								
	128.57 EUR 128.57 EUR	23.99 EUR 23.99 EUR	11.99 EUR 11.99 EUR	18.27 EUR 18.27 EUR	4.06 EUR 4.06 EUR	205.32 EUR 205.32 EUR	172.11 EUR 172.11 EUR	1.68 EUR 1.68 EUR
Support
Frequency range	ATLO-DB-2/RX
Cards support	Unique EM 125kHz	2.4 GHz	...
Signaling mode	LED indication
Reading distance of pro-keys	max. 15 cm
Operation range	max. 150 m in open area
Autonomous operation	✓
Frequency band	433 MHz
Doorbell button	—
Material	• Expansion plug, Polypropylene • Screw, Steel galvanized • mounting screw, Steel galvanized
Antenna type	1 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector), 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)	...
Relay contacts load	1.5 A / 30 V
Drilling diameter	12 mm
Battery backup support	—
Expansion plug length	155 mm
Keyboard built-in	—
Supported HDMI resolutions	480p, 576i, 576p, 720p 1080i, 1080p, 4K x 2K, 4K UHD
Standards	IEEE 802.11 b/g/n, 4G+ Cat.6 LTE, 3G	...
Input lines	3
Output lines	3
Mounting standard	...	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400, 600 x 400	VESA 100, 150, 200, 200x100, 300, 300x200, 400x200 400x300, 400	VESA 100 x 100, 75 x 75
Screw dimensions	Ø 8 x 160 mm, Internal thread M5
Tamper output	✓
Screen size range	...	36 ° ... 70 °	32 ° ... 70 °	13 ° ... 27 °
Screw	Ø 5 x 16 mm
Communication	• RS-485 • RACS (Roger)
Bearing capacity	...	50 kg	75 kg	8 kg
Application	for Styrofoam 100 mm
Distance from mounting surface	...	75 ... 400 mm	47 mm
Color	...	Black	Black	Black
Maximal transmission range	• 70 m UTP cat. 6 @ 4K UHD, • 70 m UTP cat. 5, 5e @ 1080p • 50 m UTP cat. 5e @ 4K UHD (our tests result)
Average current consumption	50 mA
Tilt adjustment	...	0 ° ... 10 °	-10 ° ... 4 °	-60 ° ... 60 °
Main features	• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 300 / 42 Mbps (4G / 3G)	...
Horizontal rotation	...	-90 ° ... 90 °	...	360 °
Rotation in the plane of the screen	...	± 3 °	...	360 °
LAN ports	• 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN	...
Environment class	IV
"Index of Protection"	IP67	IP44
Transmitter power	≤ 17.51 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA	...
LED indicators	Power, WAN, WLAN, LAN, LTE - 3G/4G, Signal indicator	...
Network type	4G, 3G	...
LTE	✓	...
QSS	—	...
WDS	—	...
DHCP server	✓	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Protections	<ul style="list-style-type: none"> • WPA3-EAP • WPA3-SAE • WPA2-Enterprise - PEAP • WPA2-PSK • AES-CCMP • WEP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering 	...
Management interface	Web browser, Teltonika RMS application, SMS	...
Main features	<ul style="list-style-type: none"> • Unique EM 125kHz proximity reader built-in • PKI series readers support • 4000 indexed users • History of 32000 events • 99 General Purpose Schedules • 250 access groups • Tamper detection - removing from mounting surface 	<ul style="list-style-type: none"> • Mount tube length 40 cm • Distance 17 cm in the bolt axis 	...	<ul style="list-style-type: none"> • Very good image quality with no visible distortions caused by compression • No delays in video transmission • No delays in mouse control operations • Transition of the HDMI signal in the transmitter • S/PDIF output 	<ul style="list-style-type: none"> • Support for IoT (Internet of Things) systems, • Ability to work as a Hotspot, • Support for VoIP technology, • SIM socket • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems 	...
Power supply	10 ... 15 V DC	Electromagnetic transducer	<ul style="list-style-type: none"> • Transmitter 5 V DC / 2 A (power adapter included) • Receiver 5 V / 2 A (power adapter included) 	<ul style="list-style-type: none"> • 9 V DC / 1 A (power adapter included) • 9 ... 30 V DC • 9 ... 30 V DC - Passive PoE, Powering from LAN1
Power consumption	≤ 6.5 W	...
Operation temp	-25 °C ... 60 °C	-20 °C ... 60 °C	-40 °C ... 75 °C
Permissible relative humidity	10 ... 95 % (non-condensing)	0 % ... 90 % (non-condensing)	10 % ... 90 % (non-condensing)
Weight	0.15 kg	4.52 kg	2 kg	2.07 kg	0.04 kg - Doorbell button	...	0.29 kg	0.13 kg
Dimensions	85 x 85 x 27 mm	640 x 420 x (75 ... 400) mm	570 x 430 x 47 mm	515 x 262 x 117 mm	75 x 40 x 20 mm	...	150 x 107 x 28 mm - Transmitter or receiver dimensions	83 x 80 x 25 mm
Manufacturer / Brand	ROGER	RED EAGLE	Teltonika	EBOLT
Guarantee	3 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00