



	IP VANDALPROOF CAMERA DS-2CD1147G2H-LIU(2.8MM) Smart Hybrid Light - 3.7 Mpx Hikvision	OVERVOLTAGE LIMITER AXON-VIDEO/TWIST
		
	79619.05 HUF 79619.05 HUF	1523.81 HUF 1523.81 HUF
Nominal voltage	...	6 V
Standard	IP	...
Maximal voltage	...	10 V
Nominal discharge current line-PG [C2]	...	5 kA (8 / 20 µs)
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Maximal discharge current (line-PG)	...	25 kA (10 / 1000 µs)
Sensor	1/3 " Progressive Scan CMOS	...
Lens	2.8 mm	...
Voltage protection level line-PG [C2]	...	1000 V
View angle	96 °	...
Range of IR illumination	30 m	...
Protection voltage Up line-line for nominal current [C3]	...	16 V
White light LED illuminator range	30 m	...
Memory card slot	—	...
Serial impedance per line	...	2 Ω
Bandwidth	...	0 MHz ... 30 MHz
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Connectors	...	2x triple screw terminal, removable, 3.5 mm distance
Protection parameters compliance	...	Compliance with PN-EN61643-21
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Noise and echo reduction 	...
Main stream frame rate	<ul style="list-style-type: none"> • 20 fps @ 4 Mpx • 25 fps @ 1080p 	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...

Max. number of on-line users	6	...
ONVIF	✓	...
Main features	<ul style="list-style-type: none"> • Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Sharpness - sharper image outlines • video tampering • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) 	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 7.5 W @ PoE • ≤ 6 W @ 12 V DC 	...
Housing	Dome, Metal + Plastic	Metal, black
Color	White	...
"Index of Protection"	IP67	...
IK rating	IK08	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.48 kg	0,07 kg
Dimensions	Ø 121 x 98 mm	69 x 33 x 20 mm
Supported languages	English, Ukrainian	...
Manufacturer / Brand	Hikvision	...

SAP Code	311325112	...
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00