



	<a href="#">ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTI-AI80FQRTD 4.5 mm - 1080p</a>	<a href="#">PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412302 1+2 TYPE 50 kA LEGRAND</a>
		
	17307.69 HUF 17307.69 HUF	19228.85 HUF 19228.85 HUF
Rated voltage	...	230 / 400 V AC, 50 / 60 Hz
Scanning system	Progressive	...
Maximal voltage	...	320 V AC, 50 / 60 Hz
Optical zoom	—	...
Class	...	1+2 type ( Class B+C )
Sensor	1/2.9 " GC2093 1/2.9 " GC2053	...
Protection level Up	...	1.2 kV @ 10/350 µs (T1) 1.7 kV @ 8/20 µs (T2)
Matrix size	2.1 Mpx 2 Mpx	...
Lens	4.5 mm 4.5 mm	...
Nominal discharge current	...	8 kA @ 10/350 µs (T1) 20 kA @ 8/20 µs (T2)
Maximum stroke current	...	50 kA @ 8/20 µs (T2)
Cards support	13.56 MHz S50	...
Operation state indication	...	✓
Keyboard built-in	—	...
Main features	...	Varistor
Doorbell button	—	...
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p 640 x 480 px	...
View angle	66 ° 66 ° 90 °	...
Interface	USB, RS-232 TTL	...
Maximum background illumination	100 000 Lux	...

QR codes reading	<ul style="list-style-type: none"> <li>• 1D : EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codabar, Interleaved 2 of 5 (ITF), ITF-6, ITF-14, ISBN, ISSN, MSI-Plessey, GS1 Databar, Code 11, Industrial 25, Standard 25, Plessey, Matrix 2 of 5</li> <li>• 2D : QR Code, Data Matrix, PDF417, Aztec</li> </ul>	...
Reading distance	<ul style="list-style-type: none"> <li>• EAN13 (13 mm) : 30 ... 140 mm</li> <li>• Code 39 (5 mm) : 30 ... 50 mm</li> <li>• QR Code (20 mm) : 35 ... 120 mm</li> <li>• Data Matrix (10 mm) : 30 ... 70 mm</li> <li>• PDF417 (6.67 mm) : 30 ... 80 mm</li> </ul>	...
Minimal contrast	25 %	...
Standard	TCP/IP	...
Range of IR illumination	5 m	...
White light LED illuminator range	5 m	...
Temperature measurement	✓	...
Temperature measurement range	35.7 °C ... 42 °C	...
Accuracy of temperature measurement	± 0.3 °C	...
Temperature measurement distance	0.7 m ... 1.2 m	...
Face recognition distance	0.5 m ... 2.0 m (max 30 000 faces in the database)	...
Internal memory	Support storage of 50 000 records	...
Video output	—	...
RS-485 interface	✓	...
Wiegand interface	✓	...
Memory card slot	—	...
Alarm inputs / outputs	0 / 1	...
Audio	Speaker built-in	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4, TCP/IP, HTTP, MQTT, RTSP, SMTP, NTP	...
WEB Server	Built-in	...
ONVIF	—	...
Default IP address	DHCP / 192.168.1.88	...

Default admin user / password	admin / 12345	...
Web browser access ports	80	...
PC client access ports	80	...
Main features	<ul style="list-style-type: none"> <li>• Built-in LCD display showing the image from the video camera and the result of temperature measurement - 800 x 1280 px, 8 "</li> <li>• Wiegand 34/26</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• RESET button</li> <li>• Alarm output of NO/NC relay type</li> <li>• Relay output operating modes: access control or notification of an exception</li> <li>• Built-in QR code reader</li> </ul>	...
Power supply	12 V / 2 A DC	...
Power consumption	≤ 18 W	...
Housing	Compact - Metal	Plastic
Color	Silver	...
"Index of Protection"	—	...
Operation temp	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)	...
Weight	1.8 kg	0.098 kg
Dimensions	366 x 132 x 144 mm	62 x 54 x 17 mm
Montage hole diameter	35 mm	...
Length of the cable	65 cm	...
Supported languages	English, French, Spanish, Ukrainian, Italian	...
Manufacturer / Brand	APTI	LEGRAND
Guarantee	3 years	2 years