





| | | | | |
|-------------------------------------|---|--|---|---|
| | POWER DISTRIBUTION UNIT LE-049470 (3 OUTLETS) 1.5 m LEGRAND | ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT DS-K1TA70MI-T - 1080p Hikvision | NVR NVR2108-I2 8 CHANNELS DAHUA | USB 3.0 ETHERNET NETWORK ADAPTER TL-UE300 TP-LINK |
| |  |  |  |  |
| | 107.30 NOK 107.30 NOK | 20120.77 NOK 20120.77 NOK | 2345.68 NOK 2345.68 NOK | 196.99 NOK 196.99 NOK |
| Supported standards | ... | ... | ... | Gigabit Ethernet |
| Rated voltage | 230 V AC / 50 Hz | ... | ... | ... |
| Chipset | ... | ... | ... | RTL8153 |
| Supported resolutions | ... | ... | max. 12 Mpx | ... |
| Total maximal current | 16 A | ... | ... | ... |
| Supported transmission speeds | ... | ... | ... | 10 / 100 / 1000 Mbps |
| Scanning system | ... | Progressive | ... | ... |
| Maximal total load | 3680 W | ... | ... | ... |
| Interface | ... | ... | ... | USB 3.0 |
| Video outputs | ... | ... | 1 pcs HDMI 4K 1 pcs VGA | ... |
| Number of outlets | 3 grounded outlets 16A/250V CEE 7/5 | ... | ... | ... |
| Resolution | ... | 1920 x 1080 - 1080p | ... | ... |
| Fuse | — | ... | ... | ... |
| Audio support | ... | ... | 8 Channels - Audio from cameras | ... |
| Switch | — | ... | ... | ... |
| Audio inputs | ... | ... | 1 pcs CINCH | ... |
| Sensor | ... | CMOS Uncooled VOx microbolometer | ... | ... |
| Wire gauge | 3 x 1.0 mm ² | ... | ... | ... |
| Ports | ... | ... | ... | • 1 x RJ45, • 1 x USB 3.0 - A type |
| Audio outputs | ... | ... | 1 pcs CINCH | ... |
| Matrix size | ... | 2.1 Mpx 120 x 160 px | ... | ... |
| Length of the cable | 1.5 m | ... | ... | ... |
| Temperature measurement | ... | ✓ | ... | ... |
| Operating system | ... | ... | ... | Windows XP/Vista/7/8/10, Linux, Mac OS, Chrome |
| Temperature measurement range | ... | 30 °C ... 45 °C | ... | ... |
| Accuracy of temperature measurement | ... | ± 0.5 °C | ... | ... |
| Image compression method | ... | ... | H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG | ... |
| Temperature measurement distance | ... | 0.3 ... 1.8 m | ... | ... |
| USB | ... | ... | 2 pcs USB 2.0 | ... |
| Certificates | ... | ... | ... | FCC, CE |
| Cards support | ... | 13.56 MHz S50 | ... | ... |
| Supported hard drives | ... | ... | 1 x 10 TB SATA III | ... |
| Reading distance of prox-keys | ... | ~ 5 cm | ... | ... |
| Recording modes | ... | ... | Manual, Sensor, Motion detection, Schedule | ... |
| Face recognition distance | ... | 0.3 m ... 1.8 m | ... | ... |
| Memory | ... | Memory of 6000 face templates Memory of 6000 RFID cards Non-volatile log buffer of the last 100 000 events | ... | ... |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | |
|------------------------------------|--------------------|--|--|-----|
| Standard | ... | TCP/IP | TCP/IP | ... |
| IR illuminator | ... | ✓ | ... | ... |
| LED illuminator | ... | ✓ | ... | ... |
| Video output | ... | — | ... | ... |
| RS-485 interface | ... | ✓ | ... | ... |
| Memory card slot | ... | — | ... | ... |
| Audio | ... | Speaker built-in | ... | ... |
| Network interface | ... | 10/100/1000 Base-T (RJ-45) | ... | ... |
| Network protocols | ... | TCP/IP | HTTP, HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, DDNS, Alarm Server, P2P, ONVIF | ... |
| External storage devices backup | ... | ... | Backup to USB drive (pendrive, external drive) | ... |
| WEB Server | ... | — | ... | ... |
| ONVIF | ... | — | ... | ... |
| RS-485 | ... | ✓ | ... | ... |
| Searching and playback the records | ... | ... | Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function | ... |
| Bitrate | ... | ... | max. 80 Mbps | ... |
| Network functions | ... | ... | Full support via network, Remote records copying, Web-Server built-in | ... |
| Mobile phones support | ... | ... | Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application | ... |
| Default IP address | ... | 192.168.1.64 | 192.168.1.108 | ... |
| Default admin user / password | ... | admin / - The administrator password should be set at the first start | admin / - The administrator password should be set at the first start | ... |
| Web browser access ports | ... | ... | 80, 37777 | ... |
| PC client access ports | ... | port 8000 | 37777 | ... |
| Mobile client access ports | ... | ... | 37777 | ... |
| RTSP URL | ... | ... | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream | ... |
| Power consumption | ... | ≤ 24 W | ... | ... |
| Alarm inputs / outputs | ... | 2 / 1 | — | ... |
| Housing | Plastic | Compact - Metal | ... | ... |
| PTZ control | ... | ... | IP Speed Dome Cameras | ... |
| Color | White / Light gray | Silver + Black | ... | ... |
| Motion Detection | ... | ... | 22 x 18 motion zones - after motion detection records detected channels only | ... |
| "Index of Protection" | ... | — | ... | ... |
| Intelligent image analysis | ... | ... | ✓ | ... |
| Mouse support | ... | ... | ✓ | ... |
| Operation temp | ... | 0 °C ... 50 °C | ... | ... |
| IR remote controller in the set | ... | ... | — | ... |
| SAP Code | ... | 302917212 | ... | ... |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | |
|----------------------|------------------|---|---|---|
| Main features | ... | <ul style="list-style-type: none"> • Detection of people without a mask - access denied or voice alerts • Temperature measurement • 7 " capacitive touch screen - 1024 x 600 px • Mechanical tamper protection • Wiegand 34/26 • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto) • AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature | <ul style="list-style-type: none"> • Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians, • classification of people and vehicles, • Face recognition and analysis in real time (up to 12 photos per second) : <ul style="list-style-type: none"> - Comparison of faces with images from the database - Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) - Real-time search of people on the basis of given side information in the range corresponding to features recognized by artificial intelligence of the device <ul style="list-style-type: none"> - Support for up to 10 face databases, including 5000 face images - Face bases can be used globally or locally for one video channel - depending on the need - In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle | <ul style="list-style-type: none"> • Compact folding design • Operation status LED indicator • Plug & Play |
| Power supply | ... | 12 V DC / 2 A (power adapter not included) | 12 V DC / 1.5 A (power adapter included) | ... |
| Weight | 0.29 kg | 1.34 kg | 0.45 kg | 0.024 kg |
| Dimensions | 165 x 53 x 38 mm | 117 x 290 x 35 mm (without bracket) | 206 x 205 x 48 mm | <ul style="list-style-type: none"> • 71 x 26 x 16 mm • Length of the cable : 35 mm |
| Supported languages | ... | Polish, English, French, Spanish, Portuguese, Russian, Italian | Polish, English, Bulgarian, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Slovenian, Serbian, Swedish, Hungarian, Italian | ... |
| Manufacturer / Brand | LEGRAND | Hikvision | DAHUA | TP-LINK |
| Guarantee | 2 years | 3 years | 3 years | 2 years |