





	MODULAR BELL OR-DP-SB-133 ORNO	EXPANSION PLUG KW-8/5X50 KLIMAS	INSULATING SHIELD BOX LE-001356 FOR MODULES MOUNTED ON DIN TS-35 RAIL LEGRAND	ACCESS CONTROLLER MODULE MC16-PAC-ST-3 ROGER
				
	5.28 EUR 5.28 EUR	0.12 EUR 0.12 EUR	1.63 EUR 1.63 EUR	424.52 EUR 424.52 EUR
Device type	Bell
Compliance with standards	PN-EN 60439-3	...
Number of served transitions	3 (two-way)
Number of supported readers	12
Rated voltage	230 V AC, 50 / 60 Hz
Current consumption	22 mA
Material	...	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized
Number of users	unlimited (purchase of the appropriate license required)
Power consumption	5 W
Drilling diameter	...	8 mm
Expansion plug length	...	50 mm
Operation state indication	—
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Buffer memory	8 000 000 events buffer
Connectors type	screw terminals max. 2.5 mm ²
Screw dimensions	...	Ø 5 x 50 mm, PZ-2
Number of access zones	6
Number of alarm zones	6
Application	...	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick
Battery backup support	12 V / 7 Ah
Housing	Plastic, DIN, TS-35 rail mounting
Color	White	...	White - RAL9010	...
Communication	<ul style="list-style-type: none"> Ethernet - RJ-45 socket RACS 5 v2 (Roger) RS-485 interface
"Index of Protection"	IP20	...	IP30	...
Width in 17.5 mm modules	1	...	2	...

Main features	<ul style="list-style-type: none"> • Electromechanical bell - 1 tone • Volume : 80 dB 	...	Heat resistance : 85 °C	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	-20 °C ... 40 °C	5 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)
Weight	0.074 kg	...	0.09 kg	0.14 kg
Dimensions	67 x 79 x 18 mm	...	140 x 52 x 68 mm	175 x 72 x 30 mm
Manufacturer / Brand	ORNO	KLIMAS	LEGRAND	ROGER
Guarantee	2 years	2 years	2 years	3 years