



	<a href="#">SWITCH POE NSW2020-6T-POE-IN 4-PORT UNIVIEW</a>	<a href="#">HUB USB 3.0 MH4PU-SV-BP</a>
		
	59.21 GBP 59.21 GBP	15.69 GBP 15.69 GBP
Connectors	...	<ul style="list-style-type: none"> <li>• 1 x plug - USB-A</li> <li>• 4 x socket - USB-A</li> </ul>
Length of the cable	...	150 cm
USB standard	...	3.0
LAN ports	<ul style="list-style-type: none"> <li>• 4 x RJ45 10/100 Base-T ( 4 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 100 Base-T - Uplink</li> </ul>	...
Management	—	...
LED diodes	Link/Act, Power, PoE Max	...
Transmission speed	<ul style="list-style-type: none"> <li>• 100 Mbps : 2 LAN ports - Uplink,</li> <li>• 10 / 100 Mbps : 4 LAN &amp; PoE ports</li> </ul>	...
Maximal output power	30 W / port PoE 802.3af/at	...
Maximal total power	60 W	...
MAC addresses table	1k	...
Operation modes	<ul style="list-style-type: none"> <li>• Extend : 250 m, 10 Mbps</li> <li>• Default : 100 m, 100 Mbps</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• EXTEND mode - ports 1, 2, 3, 4 support transmission up to 250 m</li> <li>• High priority ports : 1, 2</li> <li>• Data Flow Control</li> <li>• Buffer optimization</li> <li>• Metal housing</li> <li>• Possibility to mount to the wall</li> </ul>	<ul style="list-style-type: none"> <li>• Solid workmanship</li> <li>• Can be mounted on the edge of a tabletop or monitor frame using an integrated screw clamp</li> </ul>
Certificates	CE, FCC	...
Housing	Desktop, Metal	Aluminum + Plastic
Power supply	• 48 V DC / 1.35 A (power adapter included)	...
Operation temp	0 °C ... 40 °C	...
Weight	0.18 kg	0.09 kg
Dimensions	108 x 100 x 26 mm	89 x 46 x 23 mm
Manufacturer / Brand	UNIVIEW	ORICO
Guarantee	2 years	2 years