



	ACCESS CONTROLLER ASC3202B DAHUA	ACCESS CONTROLLER WITH FACE RECOGNITION DS-K1T341AM-S - 720p Hikvision
		
	806.40 AUD 806.40 AUD	774.63 AUD 774.63 AUD
Number of served transitions	2	...
Sensor	...	CMOS
Support	Cooperation with the access control systems	...
Matrix size	...	2 Mpx
Resolution	...	1280 x 720 - 720p
Number of supported readers	<ul style="list-style-type: none"> • 2 pcs RS-485, • 2 pcs Wiegand 	...
Battery backup support	—	...
Cards support	...	13.56 MHz S50
Face recognition distance	...	0.3 m ... 1.5 m
Memory	...	<ul style="list-style-type: none"> • Memory of 1500 face templates • Memory of 1500 RFID cards • Non-volatile log buffer of the last 150 000 events
Standard	...	TCP/IP
IR illuminator	...	—
LED illuminator	...	—
Communication	<ul style="list-style-type: none"> • 3 x RS-485, • 2 x Wiegand 34/26, • 1 x Ethernet 10 / 100 Mbps (RJ-45) 	...
Video output	...	—
RS-485 interface	...	✓
Memory card slot	...	—
Alarm inputs / outputs	2 / 2	—
Audio	...	Speaker built-in
Network interface	...	10/100/1000 Mbps (RJ-45)
Operation modes	<ul style="list-style-type: none"> • Main control mode • Sub control mode 	...
Network protocols	P2P, IPv4, DNS, DDNS, TCP, UDP, ONVIF CGI	TCP/IP, ISUP, ISAPI
WEB Server	...	Built-in
ONVIF	...	—

Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	port 8000
Main features	...	<ul style="list-style-type: none"> • 4.3 " capacitive touch screen • Mechanical tamper protection • WDR - Wide Dynamic Range • AI detection : Face recognition • Configuration and management from the iVMS-4200 application • Port USB • Recording of information about Time&Attendance • Possibility to open the gate using a QR code • Door lock control output • Possibility to connect an exit button and a reed switch to control the door status
"Index of Protection"	...	—
Operation temp	...	-30 °C ... 60 °C



Main features	<ul style="list-style-type: none"> • Support for 2 doors (2x door sensor, 2x exit button, 2x alarm line, 2x lock control) • 1000 indexed users • Support up to 3000 finger prints • Memory of 5000 RFID cards • Support storage of 300 000 records • 128 General Purpose Schedules • Identification modes : RFID card, remote access, PIN, Fingerprint - Any combination of the above • Tamper protections • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Beep signal - Buzzer • White list, Black list • Web-Server built-in • Software update via network • Monitoring and configuration through network - SmartPSS Lite application • Power output 12 V DC / 1 A - supplying power to the lock • Support hardware I/O port configuration and export configuration diagrams • ONVIF compliance 	...
Power supply	<ul style="list-style-type: none"> • 12 V DC / 2.5 A • PoE (802.3at) 	12 V DC / 2 A (power adapter included)
Power consumption	<ul style="list-style-type: none"> • ≤ 2 W (standby) • max. 20.4 W @ 12 V (operation) • max. 14.4 W @ PoE (operation) 	≤ 24 W



Supported languages	...	English, German, French, Polish, Czech, Hungarian, Bulgarian, Serbian, Slovenian, Albanian
Housing	Plastic (PC + ABS)	Metal
Color	White	Black / Silver
SAP Code	...	302917454
IK rating	IK06	...
Operation temp	-10 °C ... 55 °C	...
Permissible relative humidity	5 % ... 95 % (non-condensing)	...
Weight	0.72 kg	0.31 kg
Dimensions	186 x 186 x 58 mm	173 x 83 x 23 mm (without bracket)
Manufacturer / Brand	DAHUA	Hikvision
Guarantee	3 years	3 years