

	<a href="#">NVR TC-R31640 SPEC:E/B/N/V4.0 40 CHANNELS TIANDY</a>	<a href="#">END CLAMP PV-KK/35-50/B FOR SOLAR PANELS 35 mm</a>	<a href="#">RJ-45 FINAL SOCKET LE-764571 Niloe LEGRAND</a>	<a href="#">SWITCH POE PFS3006-4ET-60-V2 4-PORT DAHUA</a>
				
	4516.59 EUR 4516.59 EUR	0.62 EUR 0.62 EUR	7.18 EUR 7.18 EUR	47.36 EUR 47.36 EUR
Material	...	Aluminum	...	...
Standard	IP	...	...	...
Mount	...	...	Ø 60 mm (flush mounting box), Claw or screw mounting	...
Height	...	35 mm	...	...
Supported resolutions	max. 16 Mpx	...	...	...
Material	...	...	Plastic	...
Hole diameter	...	9 mm	...	...
mounting screw	...	—	...	...
Video outputs	2 pcs HDMI 4K 2 pcs VGA Video outputs are independent of each other	...	...	...
Application	...	...	RJ-45	...
Audio support	Audio from cameras	...	...	...
Application	...	...	Niloe product series	...
Audio inputs	1 pcs	...	...	...
Number of outputs	...	...	1	...
Audio outputs	1 pcs	...	...	...
Color	...	Black	White	...
LAN ports	...	...	...	<ul style="list-style-type: none"> <li>• 2 x RJ45 10 / 100 Mbps - Uplink,</li> <li>• 4 x 10 / 100 Mbps ( 1 x Hi-PoE + 3 x PoE (802.3af/at) )</li> </ul>
Image compression method	S+265 / H.265 / S+264 / H.264	...	...	...
Supported hard drives	16 x 18 TB SATA + 1 x eSATA	...	...	...
Management	...	...	...	—
Recording modes	Manual, Motion Detection, Schedule	...	...	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...	...	...
LED diodes	...	...	...	Power, PoE, Link/Act
Searching and playback the records	<ul style="list-style-type: none"> <li>• Records searching: by time and events type. Records playback: forward, backward, fast, slow</li> <li>• Advanced searching (to the one second accuracy)</li> <li>• Playback max. 16 cameras in the same time</li> </ul>	...	...	...
Transmission speed	...	...	...	10 / 100 Mbps : 2 LAN ports + 4 LAN & PoE ports

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Maximal total power	...	...	...	60 W
MAC addresses table	...	...	...	2k
Operation modes	...	...	...	<ul style="list-style-type: none"> <li>• Extend On : 250 m, 10 Mbps</li> <li>• Extend Off : 100 m, 100 Mbps</li> </ul>
Network interface	2 x RJ-45 - 10 / 100 / 1000 Mbps	...	...	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	...	...	...
Main features	...	...	<ul style="list-style-type: none"> <li>• It is compatible with Category 5e,</li> <li>• Convenient system for twisted-pair mounting requires no tools</li> </ul>	<ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• PoE power mode : The device supports 8-pin power supply</li> <li>• Intelligent management of Power Supply Unit power's output stage</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Watchdog PoE / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> <li>• Kensington Lock</li> </ul>
ONVIF	✓	...	...	...
Certificates	...	...	...	CE, FCC
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EasyLive Plus</a></li> <li>• iOS (iPhone): Free application <a href="#">EasyLive Plus</a></li> </ul>	...	...	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...	...	...
Bitrate	max. 640 Mbps	...	...	...
Operation temp	...	...	...	-10 °C ... 55 °C
Default admin user / password	admin / - The administrator password should be set at the first start	...	...	...
Default IP address	192.168.1.3	...	...	...
RTSP URL	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream	...	...	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...	...	...
PC client access ports	3000, 3001	...	...	...
Mobile client access ports	3000, 3001	...	...	...
Alarm inputs / outputs	16 / 4	...	...	...
Motion Detection	✓	...	...	...
Intelligent image analysis	—	...	...	...
USB	2 x USB 2.0 + 1 x USB 3.0	...	...	...
RS232	1 pcs	...	...	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RS485	2 pcs	...	...	...
Mouse support	✓	...	...	...
IR remote controller in the set	—	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Possibility of operation the disks in RAID JBOD/0/1/5/6/10 array</li> <li>Support for Intelligent Image Analysis function, available in TIANDY cameras : <ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• abandoned/missing object</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• parking detection</li> <li>• heat map</li> <li>• scene changing</li> <li>• signal loss indication</li> <li>• License plate recognition</li> <li>• detection of persons on duty</li> <li>• detection of people gathering</li> <li>• Parking monitoring mode</li> <li>• protective helmet detection</li> <li>• people counting</li> <li>• advanced face capture features (max 100 000 faces in the database)</li> </ul> </li> </ul>	...	...	...
Power supply	100 V ... 240 V AC	...	...	53 V DC / 1.22 A (power adapter included)
Weight	11.8 kg	0.22 kg	0.040 kg	0.29 kg
Dimensions	540 x 445 x 133 mm	50 x 38 x 28 mm	76 x 76 x 36 mm	130 x 85 x 26 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Dutch, Korean, French, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	...	...	...
Manufacturer / Brand	TIANDY	...	LEGRAND	DAHUA
Guarantee	3 years	2 years	2 years	3 years

