




	ACCESS CONTROLLER ASC2104B-T DAHUA	ACCESS CONTROLLER MC16-PAC-ST-2-KIT ROGER
		
	1477.89 DKK 1477.89 DKK	3946.42 DKK 3946.42 DKK
Number of served transitions	4 (two-way)	2 (two-way)
Support	DAHUA ASC2204C-H	...
Number of supported readers	4 pcs	8
Number of users	...	unlimited (purchase of the appropriate license required)
Output lines	5 pcs - Relay	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Alarm inputs / outputs	1 / 1	...
Buffer memory	...	8 000 000 events buffer
Number of access zones	...	4
Number of alarm zones	...	4
Battery backup support	—	12 V / 20 Ah
Communication	<ul style="list-style-type: none"> • RS-485, • Wiegand 34/26, • Control panel CAN (Controler Area Network) 	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface
Main features	<ul style="list-style-type: none"> • 20 000 indexed users • History of 30 000 events • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Door Left Open and Door Forced Open alarms • Watchdog built-in • Possibility to mount on a wall, or on the DIN TS-35 rail 	<ul style="list-style-type: none"> • Metal housing • The MCX2D I/O expander included • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128
Power supply	12 V DC / 1 A	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	-30 °C ... 60 °C	5 °C ... 40 °C
Permissible relative humidity	max. 95 % (non-condensing)	10 % ... 95 % (non-condensing)

Weight	0.384 kg	4.25 kg
Dimensions	209 x 117 x 51 mm	405 x 365 x 123 mm
Manufacturer / Brand	DAHUA	ROGER
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00