





	WIRELESS VIDEO DOORBELL ATLO-DBC2-TUYA Wi-Fi, Tuya Smart	ALUMINUM TRUSS MAST MK-1.5	POWER SUPPLY DISTRIBUTOR LZ-1S	AUTOTRANSFORMER ATS-110/230V
				
	1111.86 CZK 1111.86 CZK	5039.32 CZK 5039.32 CZK	135.39 CZK 135.39 CZK	1365.88 CZK 1365.88 CZK
Adapter type	Transforming
Height of the mast	...	1.5 m
Number of power inputs	2	...
Power voltage	115 V AC
Number of sections	...	1
Sensor	Progressive Scan CMOS - 2 Mpx
Number of power outputs	5	...
Output voltage	230 V AC
Wall thickness	...	1.5 mm
Maximal load	0.4 A
Material	...	Aluminum
Resolution	1920 x 1080 px - 1080p
Nominal power	100 VA
Possibility to combine to each other	...	✓
Lens	2.5 mm
Maximal power voltage	0 ... 24 V DC (typical 12V)	...
Length of the cables	0.65 m
View angle	135 °
Maximal power supply current	• 6 A terminals • 4 A 5.5/2.1 socket	...
Max. output current for single output	6 A	...
Protection type	—	Fuse 0.8 A
Construction	...	Truss of triangular cross-section : 250 x 250 x 250 mm
IR illuminator	10 m
LED illuminator	—
Supporting pillars	...	Aluminum tube Ø 35 mm
Wireless transmission range	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n
Network interface	2.4 GHz Wi-Fi

Main features	...	<ul style="list-style-type: none"> • No need for guy-wires up to 6 m height • The MK-1.5/POD base application enables laying a mast • Possibility of entering the assembled mast by the person weighing up to 100 kgs with winds up to 5 m/s • The possibility of transport in the trunk of a passenger car
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS
Power connectors type	Input : socket 2.1/5.5 mm / cable terminal (separable) Output : Cable terminals (separable)	...
Image compression method	H.264 / JPEG
Operation temp	-50 °C ... 55 °C	...
Permissible relative humidity	< 95 %	...
Manufacturer / Brand	...	DELTA	DELTA	...
Main features	<ul style="list-style-type: none"> • Micro SD memory cards up to 128GB support (possible local recording), • Motion Detection - PIR detector - Detector range 5 m, • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging • Low current consumption • Operating frequency - Wireless doorbell : 433 MHz
Mount	Surface-mounted

Power supply	<ul style="list-style-type: none"> • 3 x 18650 battery 3.7 V / 2600 mAh (not included) • 5 V DC - Charging via micro USB port (cable included)
Housing	Plastic
Color	White / Black
"Index of Protection"	IP44
Weight	<ul style="list-style-type: none"> • 0.14 kg - Wireless Video Doorbell • 0.06 kg - cover 	5.05 kg	0.097 kg	0.75 kg
Dimensions	<ul style="list-style-type: none"> • 150 x 75 x 36 mm - Wireless Video Doorbell • 162 x 82 x 47 mm - cover 	...	120 x 91 x 37 mm	121 x 71 x 45 mm
Guarantee	2 years	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00