



	<a href="#">ACCESS CONTROL PANEL CPR32-SE-BRD ROGER</a>	<a href="#">CABLE MANAGER OKR-40X40</a>
		
	154.97 EUR 154.97 EUR	1.04 EUR 1.04 EUR
Color	...	Silver
Material	...	Steel galvanized
Inputs	<ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 32</li> </ul>	...
Outputs	<ul style="list-style-type: none"> <li>• 4 pcs - Transistor outputs</li> <li>• 2 pcs - Relay outputs</li> </ul> NO/NC	...
Communication	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• RACS (Roger)</li> </ul>	...
Events memory	Non-volatile log buffer of the last 250 000 events	...
Output load	<ul style="list-style-type: none"> <li>• Transistor outputs : 1 A / 15 V DC</li> <li>• Relay outputs :</li> <li>REL1 - 1.5 A / 30 V DC</li> <li>REL2 - 5 A / 230 V AC</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• Ability to block/unblock partition at a specified time, or as per access schedule,</li> <li>• Central management of the access control system,</li> <li>• Integration with the alarm system SATEL INTEGRA,</li> <li>• History of 250 000 events</li> <li>• Electrical protection of all inputs and outputs as well as communication buses</li> <li>• DIN, TS-35 rail mounting</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• 24 V DC</li> <li>• 12 V DC</li> <li>• 18 V AC</li> </ul>	...
Battery backup support	✓	...
Operation temp	5 °C ... 40 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Dimensions	105 x 85 x 50 mm	50 x 40 x 40 mm (opening for cables entry)
Weight	0.12 kg	...
Manufacturer / Brand	ROGER	...
Guarantee	3 years	2 years