



	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1200T-Z- A-2712-S6 - 1080p 2.7 ... 12 mm - MOTOZOOM DAHUA</a>	<a href="#">WIRE PAIR DETECTOR UT-682D UNI-T</a>
		
	111.78 EUR 111.78 EUR	16.82 EUR 16.82 EUR
Tested cables	...	UTP, FTP, YTKSY
Standard	AHD, HD-CVI, HD-TVI, CVBS	...
Sensor	Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Resolution	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL	...
Main features	...	<ul style="list-style-type: none"> <li>• Continuous output voltage of the transmitter : 8 V DC</li> <li>• Polarity indicator for telephone wire pairs : <math>\pm</math> (5V ... 52V)</li> <li>• The maximum length of the telephone line : 3000 m</li> <li>• search for broken wires</li> <li>• Searching for a wire fault point</li> <li>• Detect ringing tone on telephone lines</li> <li>• Sending a constant or modulated signal to identify a selected wire in the bundle</li> <li>• Optical - sound signaling</li> </ul>
Lens	2.7 ... 12 mm - Motozoom - The camera does not have auto-focus function	...
View angle	98 ° ... 28 °	...
Operation temp	...	0 °C ... 40 °C
Range of IR illumination	60 m	...
IR illuminator support	ICR - Movable InfraRed filter	...
IR illuminator power adjustment	Automatic	...
Video output	AHD / HD-CVI / HD-TVI / CVBS - 1 V <sub>pp</sub> / 75 Ω	...
S/N ratio	> 65 dB	...

Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio support via coaxial cable - HD-CVI only</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• Motozoom lens - The control possible only from Dahua recorders in HD-CVI mode</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 8</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
OSD menu	OSD menu available via DAHUA recorder	...
Power supply	12 V DC / 530 mA	2 x 9V, type 6F22 battery (included)
Power consumption	≤ 6.4 W	...
Housing	Dome, Metal	...
Color	White	...
Vandal-proof	—	...
"Index of Protection"	IP67	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.59 kg	<ul style="list-style-type: none"> <li>• 0.12 kg - Transmitter</li> <li>• 0.1 kg - Receiver</li> </ul>
Dimensions	Ø 122 x 105 mm	<ul style="list-style-type: none"> <li>• 74 x 68 x 30 mm - Transmitter</li> <li>• 208 x 49 x 33 mm - Receiver</li> </ul>
Manufacturer / Brand	DAHUA	UNI-T
Guarantee	3 years	2 years