




	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR APTI-XB0801H-S34 8 CHANNELS	EXTENSION CABLE DC-2.1/5.5-WG-10M 10 m	TV OR MONITOR MOUNT AX-TYTAN-ALUXX
			
	105.66 EUR 105.66 EUR	6.00 EUR 6.00 EUR	104.46 EUR 104.46 EUR
Standard	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Mounting standard	VESA : 200, 300, 400 x 200, 400, 600 x 400
Connector type	...	1 x Ø 2.1/5.5 mm Straight socket 1 x Ø 2.1/5.5 mm Straight plug	...
Length of the cable	...	10 m	...
Screen size range	37 " ... 70 "
Rated voltage	...	12 V DC	...
Bearing capacity	45 kg
Video inputs	8 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Distance from mounting surface	54 ... 448 mm
Video outputs	<ul style="list-style-type: none"> • 1 pcs HDMI • 1 pcs VGA • 1 pcs Composite Video (CVBS) - BNC socket
Tilt adjustment	-15 ° ... 15 °
Audio inputs	<ul style="list-style-type: none"> • 8 - Audio support via coaxial cable, • 6 pcs CINCH
Horizontal rotation	-60 ° ... 60 °
Audio outputs	1 pcs CINCH
Rotation in the plane of the screen	± 3 °
Image compression method	H.265+ / H.265 / H.264+ / H.264

Image records resolutions	<ul style="list-style-type: none"> • AHD / HD-TVI : 8M-N - 1920 x 2160 px, 5 Mpx - 2592 x 1944 px, 5M-N - 1296 x 1944 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 3 Mpx - 2048 x 1536 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • HD-CVI : 8M-N - 1920 x 2160 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • CVBS : 960H - 960 x 576 px, • IP : max. 8.3 Mpx - 3840 x 2160 px
Recording speed adjustment	<ul style="list-style-type: none"> 8.3 Mpx IP @ 1 ... 25 fps 8M-N @ 1 ... 8 fps 5 Mpx @ 1 ... 6 fps 5M-N @ 1 ... 10 fps 4 Mpx @ 1 ... 8 fps 4M-N @ 1 ... 15 fps 3 Mpx @ 1 ... 9 fps 1080p @ 1 ... 15 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes	<ul style="list-style-type: none"> • 8 x AHD / HD-CVI / HD-TVI / CVBS + 4 x IP max. 8.3 Mpx • 6 x AHD / HD-CVI / HD-TVI / CVBS + 8 x IP max. 8.3 Mpx • 4 x AHD / HD-CVI / HD-TVI / CVBS + 10 x IP max. 8.3 Mpx • 2 x AHD / HD-CVI / HD-TVI / CVBS + 12 x IP max. 8.3 Mpx • 16 x IP max. 8.3 Mpx <p>All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras</p>
Recording modes	Motion Detection, Schedule

Supported hard drives	1 x 8 TB SATA
External storage devices backup	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time
Network functions	<ul style="list-style-type: none"> • Network Client Software (iVMS320): live view, playback and backup of the records • IE browser: live view, playback and backup of the records and configuration of the recorder parameters
Mobile phones support	Port no.: 6000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • iOS (iPhone): Free application BitVision, iOS: Free application iVMS320
Default IP address	192.168.1.88
Default admin user / password	admin / 12345
Web browser access ports	80, 5000, 554
PC client access ports	80, 5000, 554
Mobile client access ports	80, 5000, 6000
Alarm inputs / outputs	—
PTZ control	Pelco-D, Pelco-P
Motion Detection	Split the screen into zones : 22 x 18 motion zones
USB	2 pcs USB 2.0
Mouse support	✓
IR remote controller in the set	—
Power supply	12 V DC / 2 A (power adapter included)
Color	Black	Black	Silver / Black
Weight	0.82 kg	0.245 kg	4.76 kg
Dimensions	260 x 242 x 45 mm	...	720 x 435 x (54 ... 448) mm

Supported languages	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian
Country of origin	China
Manufacturer / Brand	APTI
Guarantee	2 years	2 years	2 years