




	<a href="#">CABLE USB-C/LIGHTNING/1M-GC 1 m Green Cell</a>	<a href="#">IP CAMERA DS-2CD2026G2-IU(2.8MM)(D) ACUSENSE - 1080p Hikvision</a>	<a href="#">IP CAMERA IPC2124LE-ADF28KM-G - 4 Mpx 2.8 mm UNIVIEW</a>
			
	12.40 USD 12.40 USD	255.08 USD 255.08 USD	162.11 USD 162.11 USD
Standard	...	TCP/IP	TCP/IP
Cable	USB-C plug / LIGHTNING plug	...	...
Sensor	...	1/2.8 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx	4 Mpx
Length of the cable	1 m	...	...
USB standard	2.0	...	...
Resolution	...	1920 x 1080 - 1080p , 1280 x 720 - 720p	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	...	2.8 mm	2.8 mm
View angle	...	107 °	• 101 ° (manufacturer data) • 97 ° (our tests result)
Compression	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
S/N ratio	...	...	> 52 dB
Main features	<ul style="list-style-type: none"> <li>• High noise immunity</li> <li>• 100% copper conductor</li> <li>• 2 x Cu - AWG 30 : Data + 2 x Cu - AWG 23 : Power supply</li> <li>• Solid workmanship</li> <li>• Power Delivery Technology - 87 W</li> <li>• Double shielding of the cable</li> <li>• Kevlar fiber reinforcement</li> </ul>	...	...
Range of IR illumination	...	40 m	50 m
Cable diameter	~ 3.5 mm	...	...
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—	—
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Noise suppression and echo cancellation</li> </ul>	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Audio detection</li> </ul>
Main stream frame rate	...	25 fps @ 1080p	25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
RS-485 interface	...	—	—
Network protocols	...	...	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL / TLS, IEEE 802.1x, SNMP
WEB Server	...	Built-in	Built-in
Max. number of on-line users	...	6	32
ONVIF	...	✓	✓

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	Access by a cloud (P2P) • Android: Free application <a href="#">EZView</a> • iOS (iPhone): Free application <a href="#">EZView</a>
Default IP address	...	192.168.1.64	DHCP or 192.168.1.13
Default admin user / password	...	admin / - The administrator password should be set at the first start	admin / 123456
Web browser access ports	...	80	80, 554
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	...	8000	80
Port ONVIF	...	80	80
RTSP URL	...	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	...	<ul style="list-style-type: none"> <li>• Camera from AcuSense series</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream</li> <li>• NAS - Network Attached Storage support</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• ICR - Movable InfraRed filter</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Configurable Privacy Zones</li> <li>• Image rotation and mirror</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection</li> </ul>	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette)</li> </ul>
Power supply	...	• PoE (802.3af), • 12 V DC / 500 mA	• PoE (802.3af), • 12 V DC / 540 mA
Power consumption	...	• ≤ 7 W @ PoE (802.3af) • ≤ 6 W @ 12 V DC	≤ 6.5 W
Housing	...	Compact, Metal	Compact, Metal + Plastic
Color	White	White	White
"Index of Protection"	...	IP67	IP67
Vandal-proof	...	...	—
Operation temp	...	-30 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.02 kg	0.5 kg	0.43 kg
Dimensions	...	Ø 74 x 179 mm	190 73 x 71 mm
SAP Code	...	311319835	...
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	Green Cell	Hikvision	UNIVIEW



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	2 years	3 years	3 years
-----------	---------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00