


	WHEEL BEARING GREASE LT-43 K2-LT-43/400 SPRAY 400 ml K2	MOUNT BOX FOR KEYSTONE CONNECTORS FX-MULTI/B	CONNECTION BOX PUH-4P
			
	3.31 GBP 3.31 GBP	0.64 GBP 0.64 GBP	5.89 GBP 5.89 GBP
Number of intakes	2
Place for connectors	...	1 pcs	...
Package	Spray 400 ml
Material	...	PET	...
Number of terminals	2 x 4 pcs
Color	...	Matt black	...
"Index of Protection"	IP68
Voltage insulation	450 V
Cable diameter	Ø 5 ... Ø 9 mm
Wire gauge	0.5 ... 2.5 mm ²
Application	Lubrication : • loaded slide, ball and roller bearings, • wheel bearings, • universal joints, • tracks, • cords
Guarantee	...	2 years	2 years
Main features	• LT-43 grease • Spray formulation with a straw for easy application in hard-to-reach places • Dual applicator - broad stream for application on a larger surface and precise stream (with a straw) for hard-to-reach places • It can be used in any position, even upside down
Weight	0.34 kg	0.015 kg	...
Dimensions	Ø 66 x 200 mm	59 x 36 x 29 mm	68 x 23 x 23 mm
Manufacturer / Brand	K2