




	<a href="#">IP VANDALPROOF CAMERA DS-2CD1143G2-LIU(2.8MM)PL Smart Hybrid Light - 3.7 Mpx Hikvision</a>	<a href="#">POWER CORD CABLE IEC320-C13/IEC320-C14/1.8M 1.8 m LANBERG</a>	<a href="#">ADAPTER IEC320/1XGS LANBERG</a>	<a href="#">POWER CORD CABLE CEE-77/IEC-C5 1.5 m</a>
				
	713.00 PLN 713.00 PLN	13.29 PLN 13.29 PLN	13.14 PLN 13.14 PLN	11.52 PLN 11.52 PLN
Standard	IP	...	...	...
Cable	...	IEC320 C13 socket / IEC320 C14 plug	...	Socket C5 (cloverleaf) / Power connector
Connector type	...	...	Adapter : IEC320 C14 plug / Power socket CEE 7/3 (Schuko)	...
Voltage	...	max. 250 V	max. 250 V	max. 250 V
Current	...	max. 2.5 A	max. 16 A	max. 2.5 A
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...	...	...
Sensor	1/3 " Progressive Scan CMOS	...	...	...
Lens	2.8 mm	...	...	...
View angle	98 °	...	...	...
White light LED illuminator range	30 m	...	...	...
Range of IR illumination	30 m	...	...	...
Memory card slot	—	...	...	...
Main features	...	<ul style="list-style-type: none"> <li>• 100% copper conductor</li> <li>• Very easy and quick assembly</li> <li>• Solid workmanship</li> <li>• 3 x 0.75 mm<sup>2</sup></li> </ul>	<ul style="list-style-type: none"> <li>• Application : UPS, PC, RTV,</li> <li>• Wire : 3 x 1.5 mm</li> <li>• Very easy and quick assembly</li> <li>• Corrosion resistance</li> </ul>	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Solid workmanship</li> </ul>
Length of the cable	...	1.8 m	0.2 m	1.5 m
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...	...
Alarm inputs / outputs	—	...	...	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> <li>• Noise and echo reduction</li> </ul>	...	...	...
Main stream frame rate	<ul style="list-style-type: none"> <li>• 20 fps @ 3.7 Mpx</li> <li>• 25 fps @ 1080p</li> </ul>	...	...	...
Network interface	10/100 Base-T (RJ-45)	...	...	...
WEB Server	Built-in	...	...	...
Max. number of on-line users	6	...	...	...
ONVIF	✓	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• Possibility to turn off the LED illuminator</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Configurable Privacy Zones</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> </ul>	...	...	...
Mobile phones support	<ul style="list-style-type: none"> <li>• Port no.: 8000 or access by a cloud (P2P)</li> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	...	...	...
Default IP address	192.168.1.64	...	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Web browser access ports	80	...	...	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...	...	...
Mobile client access ports	8000	...	...	...
Port ONVIF	80	...	...	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 500 mA</li> </ul>	...	...	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 7.5 W @ PoE</li> <li>• ≤ 6 W @ 12 V DC</li> </ul>	...	...	...
Housing	Dome, Metal + Plastic	...	...	...
Color	White	...	...	...
"Index of Protection"	IP67	...	...	...
Mechanical protection class	IK08	...	...	...
Operation temp	-30 °C ... 60 °C	...	...	...
Weight	0.48 kg	0.162 kg	0.16 kg	0.17 kg
Dimensions	Ø 121 x 98 mm	...	...	...
Supported languages	Polish	...	...	...
Manufacturer / Brand	Hikvision	Lanberg	Lanberg	...
SAP Code	311327289	...	...	...
Guarantee	3 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00